SWART BUYS October 2013

Red Grease II





- All Purpose Heavy
 Duty Lubricant
- Resists Water, Acids, Salts and Alkaline Chemicals
- Non-Melt Effective at Temperatures of up to 550°F
- Load Carrying
 Capabilities:
 65 Timken Load

Net Wt. 140 (397 gram

CAUTION:

EEP OUT OF REACH OF CHILDREI not take internally. See back panel dditional precautionary information P/N 74402 - Cartridge, 14 oz.

All-purpose, high-temperature, extreme pressure grease



Features

- All purpose heavy duty lubricant
- · Resists water, acids, salts, rust and alkaline chemicals
- Non-melt effective at temperatures of up to 550°F
- Load carrying capabilities: 65 Timken Load
- NLGI 2 to 2.5

Benefits

- Anti-wear additives to provide heavy duty service.
- One of very few greases able to withstand heavy shock load and impact pressures of 65 Timken load capabilities.
- Has excellent adhesive and cohesive properties.
- Resists most acids, weather, dirt, salts, spray, steam and oxidation.
- Protects equipment indoors or outdoors even under high temperatures and heavy loads. Penetration is 250-270 (ASTM D-217).



100113



PRICES EFFECTIVE OCTOBER 1ST - OCTOBER 31ST 2013



EXCEPTIONAL PRODUCTS, SERVICE AND INNOVATIVE SOLUTIONS



