

Intrinsically Safe Headlamps

Dual-Function/Class I, II, III, Division I, Groups A-G

- **Multi-position tilt head design with elastic head strap (with non-slip lining) and a heavy-duty rubber head strap for use on a hard hat**
- **Selectable high or low brightness spotlight operation**
- **CREE® LED technology – 50,000+ hours LED life**
- **High-brightness spotlight – 115/60 Lumens**
Low-brightness spotlight – 65/40 Lumens
- **Focused spotlight beam for distance illumination (92/80 meters)**
- **Waterproof: IP-X7 Rating**
- **Engineered polymer housing**
- **Single switch located on top of light**
- **Impact & chemical resistant**
- **3 AAA premium batteries (included), reorder using P/N 29204**



Safety Rating


cETLus Listed Intrinsically Safe
for use in Class I II III Div 1 SECURITE
INTRINSEQUE Groups A,B,C,D,E,F & G
Hazardous Locations -20C ≤ Tamb ≤ +40C

- Ex ia IIC T3 Ga Class 1 Zone 0
- AEx ia IIC T3 Ga, Zone 20
- AEx ia IIIC T 165C Da




High/Low brightness
spotlight switch

Spotlight




Specifications – P/N 66318

- **Spotlight Lumens:** High - 115 / Low - 65
- **Run-time:** High - 4.5 hrs / Low - 13 hrs
- **Beam distance:** 92 meters
- **Water rating:** IP-X7 waterproof
- **Drop rating:** 2 meters
- **Dim:** 2.4" width x 1.9" height x 1.8" depth
- **Weight:** 3.5 oz



Specifications – P/N 66319*

- **Spotlight Lumens:** High - 60 / Low - 40
- **Run-time:** High - 13.5 hrs / Low - 22.75 hrs
- **Beam distance:** 80 meters
- **Water rating:** IP-X7 waterproof
- **Drop rating:** 2 meters
- **Dim:** 2.4" width x 1.9" height x 1.8" depth
- **Weight:** 3.5 oz



*Non-stock item, please call for delivery.



EXCEPTIONAL PRODUCTS, SERVICE AND INNOVATIVE SOLUTIONS

5250-A Naiman Parkway . Solon . OH 44139

010114 1-800-BUY-BOLT . Fax: 631-567-2418 . www.chromate.com LIT66318

