

3M™ Fire Barrier Foam FIP 1-Step



3M™ FIP 1-Step

P/N 74588, 12.85 fl oz*

P/N 74588N, Nozzle (2 pack)

Foam-In-Place Firestop

- A smoke and firestopping foam for wall and floor penetrations.
- Used in mechanical, electrical, data and plumbing applications.
- Premium two-part, easy-to-handle formulation.
- Expands during installation and bonds to concrete, metal, wood, plastic and cable jacketing. Dries to a flexible solid.

*Includes 2 nozzles (P/N 74588N)

Finally, a UL Listed alternative to mineral wool, bricks and runny, ineffective foams.



HandyMax® HMS-G4C2 Manual Gun

P/N 9572



PowerMax® HPS-4C2 Battery-Powered Gun

P/N 9573



All items are non-stock. Please allow 1 to 2 weeks for delivery (3M factory stock). For urgent requirements, please call.



3M™ Fire Barrier Foam FIP 1-Step

This Foam Won't Roam.

It's like no firestop foam you've used before — it works. It's not runny, so it stays in place and expands at a controlled and consistent pace. Installs in vertical and horizontal applications without running down the opening or sagging. Similar to many two-part epoxy sealants, but with just one step — saving you trips up and down the ladder.

Key Features:

- Firestop tested up to 2 hours in accordance with ASTM E 814 (UL 1479) and CAN/ULC S115.
- Meets the International Building Code for Passive Fire Protection.
- Expands up to 5X when dispensed. One cartridge FIP 1-Step equals up to 6 tubes 10.1 oz caulk.
- Intumescent. Expands in a fire.
- Expansive UL systems for blank openings, metal pipe, cables, cable trays, combos, insulated pipe.
- UL systems require no mineral wool.
- Remains pliable after installation for easy installation of new cables/conduit in existing opening.
- Excellent adhesion. Can be installed in wall or floor applications with no backing material.
- STC rating of 57 when tested in STC 57 rated wall assembly.
- Air leakage less than 1 CFM/Sq Ft.
- Shelf life is 12 months in original unopened containers from date of packaging.

Typical Applications:

- Conduit banks
- Cables
- Cable trays
- Combos
- Busways
- Metal pipes
- Plastic pipes
- Insulated pipes
- HVAC duct penetrations
- Blank openings in floors and walls

IT'S ABOUT TIME.

Finish your firestop installations more than **3X faster**.
The larger the application opening, the greater the time and money savings.

% Time Savings
compared to traditional firestop methods*

Application	% Time Savings
Conduit Banks	72%
Cable Bundles	50%
Cable Trays	44%

*Time savings based on laboratory simulations. Actual time savings will vary based on complexity of application and skill of installer. Traditional methods refer to caulks, sealants, mineral wool, pillows, bricks and putty.

WE'RE NOT MESSING AROUND.

Enough with itchy mineral wool, tedious bricks and pillows, and runny, ineffective foams. Introducing 3M™ FIP 1-Step Firestop Foam — a breakthrough foam that is UL Listed for a broad range of applications and meets the International Building Code for passive fire protection. Finish your firestop installations more than 3X faster, saving you time, money and frustration. It's the real deal.

SOUND BARRIER STC 57 In STC 57-rated wall assembly	SMOKE SEAL L RATED Meets Air Leakage Requirements
FIRE BARRIER F RATED UP TO 2 HOUR	TEMPERATURE T RATED UP TO 1 HOUR

PLEASE SEE APPROPRIATE UL SYSTEM FOR ASSOCIATED RATING.

CLASSIFIED UL FILL, VOID OR CAVITY MATERIAL FOR USE IN THROUGH-PENETRATION FIRESTOP SYSTEMS SEE UL FIRE RESISTANCE DIRECTORY SOLG	ULC LISTED FILL, VOID OR CAVITY MATERIAL
---	--

IMPORTANT:

Products do not achieve ratings, systems do. Consult your UL directory for specific information regarding your application.



See FIP 1-Step in action! Scan the QR Code to go to the video.

