

RED GREASE HI-TEMP

PROFESSIONAL RED GREASE LUBRICANT



DESCRIPTION

A multi-purpose lubricant that provides extra protection under extreme pressures. It maintains constant viscosity over a wide range of temperatures.

FEATURES

- Sprays out as a liquid which sets up to a thick grease in minutes
- Penetrates, lubricates and prevents rust on all metal parts
- Contains a high pressure additive that reduces wear and extends operating life of all parts and machinery
- Prevents seizing and loosens frozen parts
- Congeals to a thick grease
- Superior long life
- Resists water washout
- Temperature range of -40°F to +575°F
- Contains corrosion inhibitors

FOR USE ON

- | | |
|--------------------|-------------|
| • Bearings | • Pulleys |
| • Motor shafts | • Hinges |
| • Roller chains | • Rollers |
| • Hitches | • Cams |
| • Bearing surfaces | • Couplings |
| • Cables | • Bushings |

P/N 74415
Net Wt. 11 oz.
(312 grams)



DANGER! EXTREMELY FLAMMABLE CONTENTS UNDER PRESSURE. EYE AND SKIN IRRITANT. HARMFUL OR FATAL IF SWALLOWED OR INHALED. CAREFULLY READ CAUTIONS ON REAR PANEL.

Net Wt. 11 oz. (312 grams)

