

HMMWV Field-Repair Push Kit

"With Case"

TEMPERATURE RATING:

Min. -10°F (-23°C) Max. +210°F (+99°C)

DIMENSIONS:

Inside 29-1/8" x 20-11/16" x 17-5/8"

Outside 31-1/2" x 22-7/8" x 18-7/8"

- Total protection for your equipment - unbreakable, watertight, dustproof, chemical resistant and corrosion proof
- Made of durable ultra high impact structural copolymer
- Exclusive 1/4" (6.4mm) polymer o-ring and ABS "easy-to-open" latches seal perfectly and include an automatic purge valve for quick equalization after changes in atmospheric pressure
- Equipped with heavy duty wheels, a retractable extension handle and multiple fold down carrying handles
- 1" foam lining on all sides and convoluted foam in lid for total subjection and protection against impact, vibration or shock

**ORDER PART #79004
AND RECEIVE ALL
8 ASSORTMENTS**

**SEE ASSORTMENT
DETAILS ON BACK**



CONTENTS SUBJECT TO CHANGE • MAY CONTAIN BOTH GSA CONTRACT ITEMS AND NON-CONTRACT ITEMS

ORDER TOLL FREE: 1-877-CHROMATE • FAX: 1-877-233-3377 • Email: GSAsupport@chromate.com



ALLOY 200 V-LOC WASHERS ASSORTMENT

- FEATURES:**
- The most reliable vibration-resistant lock washer available
 - Special chromate protective plating for durability and corrosion resistance
 - Resists vibration, lost holding power, slippage, wear and equipment breakdown
 - Use only in pairs



P/N 7703

EXPANSION			
5/16" (8 mm) P/N 6102	1/2" (12 mm) P/N 6105	3/4" (20 mm) P/N 6110	EXPANSION
1/4" (6 mm) P/N 6101	7/16" (11 mm) P/N 6104	5/8" (16 mm) P/N 6107	1" (25 mm) P/N 6112
3/16" (5 mm) P/N 6100	3/8" (10 mm) P/N 6103	9/16" (14 mm) P/N 6106	7/8" (22 mm) P/N 6111

CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLOM, OHIO 44139 • 1-800-BUY-BOLT • FAX: 631-567-2418 • www.chromate.com



DOUBLE EDGE/SPIRAL SCREW EXTRACTORS

- DOUBLE EDGE EXTRACTORS**
- Remove damaged screws and bolts without damage
 - Double edge can be used for both right and left hand threads
 - Superior non-slip engagement with screws or bolts to be removed

- SPIRAL SCREW EXTRACTORS**
- High torque and resistance for strength and durability
 - Special steel shaft for superior strength and durability
 - Durable handle made of high strength alloy steel
 - Coated handle for fast chip removal and easier turning
 - Coated handle, superior, fast and easy to use

- LEFT HAND DRILLS**
- Remove drilling, drilling system breaking
 - Special steel shaft for superior strength and durability
 - Durable handle made of high strength alloy steel
 - Coated handle for fast chip removal and easier turning
 - Coated handle, superior, fast and easy to use



P/N 17934

#1 DOUBLE EDGED SCREW EXTRACTORS PIN 12051	#4 DOUBLE EDGED SCREW EXTRACTORS PIN 12054	#1 SPIRAL SCREW EXTRACTOR PIN 13060	#4 SPIRAL SCREW EXTRACTOR PIN 13063
1/8 LEFT HAND DRILL PIN 11005	1/2 LEFT HAND DRILL PIN 11012	5/64 LEFT HAND DRILL PIN 11002	1/4 LEFT HAND DRILL PIN 11009
#2 DOUBLE EDGED SCREW EXTRACTORS PIN 12052	#5 DOUBLE EDGED SCREW EXTRACTORS PIN 12055	#2 SPIRAL SCREW EXTRACTOR PIN 13061	#5 SPIRAL SCREW EXTRACTOR PIN 13064
3/16 LEFT HAND DRILL PIN 11007	7/16 LEFT HAND DRILL PIN 11015	1/8 LEFT HAND DRILL PIN 11004	1/8 LEFT HAND DRILL PIN 11010
#3 DOUBLE EDGED SCREW EXTRACTORS PIN 12053		#3 SPIRAL SCREW EXTRACTOR PIN 13062	
1/4 LEFT HAND DRILL PIN 11009		5/32 LEFT HAND DRILL PIN 11006	

CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLOM, OHIO 44139 • 1-800-BUY-BOLT • FAX: 631-567-2418 • www.chromate.com



CIC 200™ THREAD REPAIR INSERT ASSORTMENT

- FEATURES:**
- Installs permanent threads that won't fail, strip, rotate or pull out even under excessive loading

P/N 7736

6-32 INTERNAL THREAD PIN 1654 TO INSTALL: USE #7 DRILL USE 1/4-20 TAP	1/4-20 INTERNAL THREAD PIN 1657 TO INSTALL: USE 23/64 DRILL USE 7/16-14 TAP	1/2-13 INTERNAL THREAD PIN 1661 TO INSTALL: USE 21/32 DRILL USE 3/4-10 TAP	5/16-24 INTERNAL THREAD PIN 1759 TO INSTALL: USE 27/64 DRILL USE 1/2-13 TAP
8-32 INTERNAL THREAD PIN 1655 TO INSTALL: USE 7" DRILL USE 5/16-18 TAP	5/16-18 INTERNAL THREAD PIN 1658 TO INSTALL: USE 27/64 DRILL USE 1/2-13 TAP	10-32 INTERNAL THREAD PIN 1757 TO INSTALL: USE 5/16 DRILL USE 3/8-16 TAP	3/8-24 INTERNAL THREAD PIN 1760 TO INSTALL: USE 31/64 DRILL USE 9/16-12 TAP
10-24 INTERNAL THREAD PIN 1656 TO INSTALL: USE 5/16 DRILL USE 3/8-16 TAP	3/8-16 INTERNAL THREAD PIN 1659 TO INSTALL: USE 31/64 DRILL USE 9/16-12 TAP	1/4-28 INTERNAL THREAD PIN 1758 TO INSTALL: USE 23/64 DRILL USE 7/16-14 TAP	1/2-20 INTERNAL THREAD PIN 1762 TO INSTALL: USE 21/32 DRILL USE 3/4-10 TAP

CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLOM, OHIO 44139 • 1-800-BUY-BOLT • FAX: 631-567-2418 • www.chromate.com



THININSERT / NUTSERT ASSORTMENT

- FEATURES:**
- Fast, convenient installation of threads in any blind area
 - CIC 200™ Threads and Nutserts are an easily-installed alternative to many "blind" fasteners
 - They offer strength, permanence and load-bearing capabilities for a variety of materials.

P/N 17935

6-32 STAR FLANGE THININSERT PIN 590	8-32 STAR FLANGE THININSERT PIN 591	10-32 STAR FLANGE THININSERT PIN 592	10-32 STAR FLANGE THININSERT PIN 593	1/4-20 STAR FLANGE THININSERT PIN 594
6-32 ADAPTER FOR QUIK TOOL PIN 483	8-32 ADAPTER FOR QUIK TOOL PIN 484	10-32 ADAPTER FOR QUIK TOOL PIN 485	10-32 ADAPTER FOR QUIK TOOL PIN 486	1/4-20 ADAPTER FOR QUIK TOOL PIN 488
6-32 STARSERT THREADED NUTSERT PIN 47901	8-32 STARSERT THREADED NUTSERT PIN 47902	10-32 STARSERT THREADED NUTSERT PIN 47903	10-32 STARSERT THREADED NUTSERT PIN 47904	1/4-20 STARSERT THREADED NUTSERT PIN 47905
5/16-18 STAR FLANGE THININSERT PIN 595	5/16-18 ADAPTER FOR QUIK TOOL PIN 490	5/16-18 STARSERT THREADED NUTSERT PIN 47907		

CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLOM, OHIO 44139 • 1-800-BUY-BOLT • FAX: 631-567-2418 • www.chromate.com



CIC 200™ CLEAR SHRINK TUBING

- FEATURES:**
- Dual wall flexible clear polypropylene tubing with thick wall adhesive
 - Clear for easy viewing of finished product
 - Operating temperature range is -47°F (-50°C) to 230°F (110°C)
 - Recommended in applications requiring moisture protection or waterproofing
 - Shrink temperature is 230°F (110°C)



P/N 17925

1/8" x 12" P/N 26090	3/16" x 12" P/N 26091
1/4" x 12" P/N 26092	
3/8" x 12" P/N 26093	
1/2" x 12" P/N 26094	
3/4" x 12" P/N 26095	
1" x 12" P/N 26096	

CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLOM, OHIO 44139 • 1-800-BUY-BOLT • FAX: 631-567-2418 • www.chromate.com



BATTERY TERMINAL REPAIR ASSORTMENT

- FEATURES:**
- Fast, convenient installation of terminals in any blind area
 - CIC 200™ Threads and Nutserts are an easily-installed alternative to many "blind" fasteners
 - They offer strength, permanence and load-bearing capabilities for a variety of materials.

P/N 17936

2GA 40 SLK 6" HYV WALL HEAT SHRINK TUBE PIN 32178	2GA 40 RED 6" HYV WALL HEAT SHRINK TUBE PIN 32180	20 GA MAGNA-LUG 10 STUD PIN 32206	1 X 36 FUSION SEAL ELEC WRAP-RED PIN 2899
MILITARY BATTERY CORN. POSITIVE PIN 2810	MILITARY BATTERY CORN. NEGATIVE PIN 2812	16-14 SUR-SEAL BUTT CONNECTOR PIN 2842	1 X 36 FUSION SEAL ELEC WRAP-RED PIN 2899
		STUD NUT PIN 32165	2-1/2 X 10' LECTRO SEAL "900" PIN 2898
		SIDE MOUNT BOLT-DEM PIN 32166	

CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLOM, OHIO 44139 • 1-800-BUY-BOLT • FAX: 631-567-2418 • www.chromate.com



HMMWV BRAKE, POWER STEERING AND ALTERNATOR REPAIR ASSORTMENT

- FEATURES:**
- Contains Chromate's high strength fasteners for lasting repairs

P/N 17933

10mm x 30mm METRIC CAP SCREW PIN 67156	1/4-20 USE TAPER LOCKNUT PIN 6800	7/16 LOCK WASHER PIN 6315	5/16 FREE SPINNING FLANGE LOCKNUT PIN 6811PS
10mm x 35mm METRIC CAP SCREW PIN 67158	10mm x 120mm METRIC CAP SCREW PIN 67178	5/16-18 x 1 GRADE 8 CAP SCREW PIN 40730	10 x 30 HEX FLANGE BOLT 10.9 PIN 69990
1/4-20 x 1 GRADE 8 CAP SCREW PIN 41004	1/4 SAE NARROW BAND FLAT WASHER PIN 9000	10 x 45 HEX FLANGE BOLT 10.9 PIN 69991	10mm METRIC FLAT WASHER PIN 67346

CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLOM, OHIO 44139 • 1-800-BUY-BOLT • FAX: 631-567-2418 • www.chromate.com



HMMWV ELECTRICAL TERMINAL ASSORTMENT

- FEATURES:**
- Contains Chromate's high strength terminals for lasting repairs

P/N 17960

16-14 x 157 SNAP PLUG PIN 2030	16-14 x 176 SNAP PLUG PIN 2029	16-14 x 157 SNAP PLUG RECEPTACLE PIN 2784	16-14 x 176 SNAP PLUG RECEPTACLE PIN 2785	156-2-WAY SNAP PLUG CONNECTOR PIN 2040	EXPANSION
16-14 x 4-6 SUR SEAL RING CONNECTOR PIN 2819	16-14 x 8-10 SUR SEAL RING CONNECTOR PIN 2820	16-14 x 1/4 SUR-SEAL RING CONNECTOR PIN 2821	16-14 x 5/16 SUR-SEAL RING CONNECTOR PIN 2822	16-14 x 3/8 SUR-SEAL RING CONNECTOR PIN 2823	EXPANSION
16-14 x 6 SUR SEAL SNAP SPADE PIN 21607	16-14 x 8 SUR SEAL SNAP SPADE PIN 21608	16-14 x 10 SUR-SEAL SNAP SPADE PIN 21609	16-14 x 1/4 SUR-SEAL SNAP SPADE PIN 21609		EXPANSION
16-14 x 1/4 SUR SEAL FULLY INSULATED FEMALE QUICK SLIDE PIN 2845	16-14 x 1/4 SUR SEAL FULLY INSULATED MALE QUICK SLIDE PIN 2844	16-14 SUR-SEAL BUTT CONNECTOR PIN 2842	4 GA MAGNA-LUG 3/8 STUD PIN 32214		EXPANSION

CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLOM, OHIO 44139 • 1-800-BUY-BOLT • FAX: 631-567-2418 • www.chromate.com