

MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

FOR CHEMICAL EMERGENCY

Call ChemTrec day/night: 1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ECO-FRIENDLY FLOOR STRIPPER

PART NUMBER: 74077 (1 gal.), 74078 (5 gal.), 74079 (55 gal.)

PRODUCT TYPE: Environmentally Friendly Alkaline Stripper

CHEM. FAMILY: Surfactant Blend

STANDARD: Meets GS-40 Green Seal[™] Standard

DOT CLASSIFICATION: Corrosive

DOT SHIPPING NAME:

Corrosive Liquid n. o. s. (Ethanolamine)8, UN 1760, PGII

DATE PREPARED: JANUARY 20, 2009

CHROMATE INDUSTRIAL CORPORATION 5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

HAZARD RATING: HEALTH: 2 FLAMMABILITY: 0 REACTIVITY: 0 PERSONAL PROTECTION: B

SECTION 2 – INGREDIENTS INFORMATION			
CHEMICAL NAME	CAS NO.	% / WT.	THRESHOLD LIMIT VALUE
DIETHYLENE GLYCOL MONOBUTYL ETHER	112-34-5	TO 25	25ppmTWA
MONOETHYLOLAMINE.	141-43-5	TO 7	3ppmTWA
SODIUM HYDROXIDE	1310-73-2	TO 6	N/A
SURFACTANT	MIXTURE	TO 1	N/A
WATER	7732-18-5	TO 63	NONE

*An asterisk indicates the toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372.

SECTION 3 – PHYSICAL DATA

BOILING RANGE (F): 212-220 °F VAPOR PRESSURE: N/D % VOLATILE: 73-74 SOLUBILITY IN WATER: Complete SPECIFIC GRAVITY: 1.04 VAPOR DENSITY: Same as Water pH: 13 EVAPORATION RATE: N/A

PHYSICAL DESCRIPTION: Clear Liquid, Mild Odor

SECTION 4 – REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will Not Occur

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids and oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Normal products of combustion

SECTION 5 – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Exceeds 200 °F

FLAMMABILITY: Non-Flammable

EXTINGUISHING MEDIA: Water, CO,

SPECIAL FIRE FIGHTING PROCEDURES: Floor may be slippery

UNUSUAL AND EXPLOSION HAZARDS: None

N/D - NOT DETERMINED

N/E - NONE ESTABLISHED

SECTION 6 – STORAGE AND HANDLING INFORMATION

SPECIAL PRECAUTIONS: Keep out of reach of children. Use only in well ventilated area. For institutional and industrial use only. For use by trained personnel only. Store and keep in closed container, in a cool place. Avoid freezing.

SECTION 7 – HEALTH HAZARD DATA

EYES: May cause severe irritation.

SKIN: May cause severe irritation.

INHALATION: May cause irritation to upper tract.

INGESTION: May cause irritation of mucous membranes.

MEDICAL CONDITION AGGRAVATED BY EXPOSURE:

Person with present skin disorder may be more susceptible to irritation.

SECTION 8 – FIRST AID PROCEDURE

EYES: Flush with running water for 15 minutes.

SKIN: Wash off with soap and water.

INHALATION: Remove to fresh air.

INGESTION: Do not induce vomiting. Drink plenty of water. If unconscious or in convulsion, take to hospital or physician.

SECTION 9 – PRECAUTIONS FOR SAFE HANDLING

RESPIRATORY PROTECTION: No special requirements.

PROTECTIVE GLOVES: Chemical resistant.

VENTILATION: Good ventilation required.

EYE CONTACT: Goggles or face shield.

SECTION 10 – SPILL OR LEAK

SPILLAGE: Dike & contain spill, absorb the liquid.

DISPOSAL: Scoop or shovel solid material into a suitable container for recovery or disposal. Area may become slippery. Flush cleaned area with water. Dispose according to local, state and federal requirements.

OTHER INFORMATION

The information presented in this MSDS has been compiled from sources deemed reliable. This MSDS is presented in good faith and believed to be accurate as of the effective date shown above. No warranty, expressed or implied, is given. Regulatory requirements are subject to change and may differ from one location to another. It is the responsibility of the buyer to insure compliance with federal, state, provincial and local laws and regulations.

Page 2 of 2

EXPOSURE LIMITS: N/E CARCINOGENICITY: NTP: N/L

IARC: N/L

OSHA: N/R