



# MATERIAL SAFETY DATA SHEET

**CHROMATE INDUSTRIAL CORPORATION®**

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL  
EMERGENCY**

Call ChemTrec day/night:  
**1-800-424-9300**

## SECTION 1 – IDENTIFICATION

**PRODUCT NAME:** PTFE DRY LUBE

**PART NUMBER:** 74116

**DATE PREPARED:** September 1, 2009

**CHROMATE INDUSTRIAL CORPORATION**

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

**PROPER SHIPPING NAME:** CONSUMER COMMODITY, ORM-D

## SECTION 2 – IDENTITY INFORMATION AND HAZARDOUS INGREDIENTS

<b>Chemical Name:</b>	<b>CAS No.:</b>	<b>TLV:</b>
Aliphatic Petroleum Distillates	64742-89-8	Not established
Propane	74-98-6	2500ppm
Isobutane	75-28-5	Not established
n-Butane	106-97-8	800ppm

## SECTION 3 – PHYSICAL DATA

**Boiling Point:** <0 to 212°F

**Specific Gravity (H<sub>2</sub>O=1):** 0.80 ± 0.05

**Solubility in Water:** Nil

**Evaporation Rate:** Slower than Ether

**Vapor Density(Air=1):** Heavier than air

**pH:** NA

## SECTION 4 – FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** 140°F

**Flash Point (Propellant):** <0°F

**Flammable Limits (Propellant):** LEL: 1.8 UEL: 9.5

**Extinguishing Media:** Use water fog, dry chemical or carbon dioxide.

**Special Fire Fighting Procedures:** Aerosol cans may rupture when heated.

**Unusual Fire and Explosion Hazards:** Heated cans may burst.

## SECTION 5 – REACTIVITY DATA

**Stability:** Unstable \_\_\_\_\_  
Stable  X

**Incompatibility (Materials to Avoid):** None known.

**Conditions to Avoid:** High temperatures.

**Hazardous Decomposition or Byproducts:** In fire, will decompose to carbon dioxide, carbon monoxide, hydrogen flouride.

**Hazardous Polymerization:** Will not occur

**SECTION 6 – STORAGE AND HANDLING INFORMATION****Precautions to be Taken in Handling and Storing:**

When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.

STORE AT TEMPERATURES BELOW 120°F

KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME

KEEP AWAY FROM CHILDREN

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

FOR USE BY TRAINED PERSONNEL ONLY

KEEP CONTAINER CLOSED DURING STORAGE

**SECTION 7 – HEALTH HAZARDS AND FIRST AID****Effects of Overexposure:**

SKIN: Skin irritant. Will cause defatting of skin. Effects are reversible.

EYES: Eye irritant. Will cause redness and burning sensation.

INHALATION: Effects of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death.

INGESTION: Aspiration hazard if swallowed.

**First Aid Procedures:**

SKIN: Immediately flush exposed area with water for at least 15 minutes. If irritation persists, get medical attention. Remove contaminated clothing and launder before reuse.

EYES: Immediately flush with large quantities of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Seek medical attention.

INHALATION: Remove person to fresh air. If irritation persists, give oxygen, get medical attention.

INGESTION: DO NOT induce vomiting. Seek medical attention immediately.  
Note: Never give anything by mouth to an unconscious or convulsing victim.  
Keep person warm and quiet.

**SECTION 8 – SPECIAL PROTECTION INFORMATION**

**Respiratory Protection:** Self-contained breathing apparatus if above TLV limit.

**Ventilation:** Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit.

**Protective Gloves:** None required if spraying.

**Eye Protection:** Recommend the use of safety glasses or chemical splash goggles.

**Other Protective Equipment:** Long sleeves and long pants.

**Work/Hygienic Practices:** Do not smoke while using. Wash hands after use.

**SECTION 9 – SPILL OR LEAK PROCEDURE**

**Steps To Be Taken In Case Material Is Released or Spilled:** Use absorbent sweeping compound to soak up material. Put into container. Dispose as hazardous waste.

**Waste Disposal Method:** Dispose as hazardous waste in accordance with EPA RCRA.

**SECTION 10 – REGULATORY INFORMATION****SARA Title III, Section 313 Components:**

Aliphatic Petroleum Distillates contain a maximum of 4% cyclohexane (110-82-7) which is subject to the reporting requirements of SARA Title III, Section 313.

This information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition. We make no warranties, express or implied, and assume no liability in connection with any use of this information. Prepared According to 29 CFR 1910.1200.