

MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

FOR CHEMICAL EMERGENCY

Call ChemTrec day/night: 1-800-424-9300

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED LION PRO-TEX DATE PREPARED: February 9, 2009
PART NUMBER: 74152 CHROMATE INDUSTRIAL CORPORATION

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

DOT Hazard Classification: ORM-D

CHEM. FAMILY: ISOBUTANE/PROPANE/ISOPROPANOL BLEND NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA

SECTION 1 – MATERIAL IDENTIFICATION AND INFORMATION

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

NFPA RATING: Health: 1 Flammability: 2 Reactivity: 0 Special: -

HMIS RATING: Health: 1 Flammability: 2 Reactivity: 0 Personal Protection: B

COMPONENTS-OSHA PEL ACGIH CARCINOGEN CAS Number SARA CHEMICAL NAMES/COMMON NAMES **III LIST** (ppm) TLV (ppm) Ref. Source ** (Hazardous Components 1% or greater; Carcinogens 0.1% or greater) **ISOPROPANOL** 67-63-0 No 400 400 d ISOBUTANE/PROPANE BLEND 75-28-5 No 800 800 d 74-98-6 Nο 1000 1000 d

SECTION 2 - PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point: N/A

Specific Gravity (H2O=1): Concentrate Only = 0.98 Vapor Pressure: PSIG @ 70°F (Aerosols): Max.70

Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A

Vapor Density (Air = 1): N/E
Evaporation Rate (= 1): N/E
Solubility in Water: Soluble

Water Reactive: No

Appearance and Odor: Chalky white color, alcohol odor.

SECTION 3 – FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols): no projection: NOT CATEGORIZED AS FLAMMABLE

Auto-Ignition Temperature: N/E

Flammability Limits in Air by % in Volume: % LEL: $\,$ N/E $\,$

% UEL: N/E FLASH POINT AND METHOD USED (non-aerosols): N/A

SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus (SCUBA).

EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.

Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/R — NOT REGULATED N/L — NOT LISTED Page 1 of 2 REV 02/09/2009 BJM

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR Incompatibility (Materials to Avoid): Strong oxidizers. Conditions to Avoid: Open flame, welding arcs, heat. Hazardous Decomposition Products: CO, CO,.

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: INHALATION and SKIN ABSORPTION

ACUTE EFFECTS

Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects

and possible unconsciousness.

Eye Contact: Possible slight irritation. Skin Contact: Possible slight irritation.

Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.

CHRONIC EFFECTS: (Effects due to excessive & abusive inhalation of propellant of this mixture)

May cause liver, kidney or brain damage.

Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention. Skin Contact: Wash with soap and water. If irritated, seek medical attention. Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

SECTION 6 – CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH for organic vapor.

Protective Gloves: Latex, if skin easily irritated. Eye Protection: Safety glasses recommended.

Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.

Other Protective Clothing & Equipment: None

Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations.

Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.

Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.

OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/R — NOT REGULATED N/L - NOT LISTED