

MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

FOR CHEMICAL EMERGENCY

Call ChemTrec day/night: 1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED LION RTV (RED HI TEMP)

DATE PREPARED: JULY 11, 2011

PART NUMBER: 74153

PRODUCT TYPE: OXIME CURE CHROMATE INDUSTRIAL CORPORATION

CHEM. FAMILY: SILICONE SEALANT 5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 2 - PRODUCT COMPONENTS

COMPONENT	CAS#	WT%	EXPOSURE LIMITS
DIMETHYL SILOXANE, HYDROXYTERMINATED	70131-67-8	> 60.0	
SILICA, AMORPHOUS	7631-86-9	7.0 - 13.0	
METHYL TRI(ETHYLMETHYLKETOXIME) SILANE	22984-54-9	3.0 - 7.0	See Ethyl Methyl Ketoxime comments
POLYDIMETHYLSILOXANE	61348-62-9	1.0 - 5.0	

COMMENTS: Ethyl Methyl Ketoxime is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within

the following exposure

GUIDELINES: VENDOR GUIDE TWA: 3 ppm STEL: 10 ppm AIHA WEEL TWA: 10 ppm

SECTION 3 - PHYSICAL / CHEMICAL CHARACTERISTICS

 PHYSICAL FORM:
 Paste
 ODOR:
 Some odor

 SPECIFIC GRAVITY @ 25°C:
 1.05
 VISCOSITY:
 N/D

 FREEZING/MELTING POINT:
 N/D
 BOILING POINT:
 N/D

 VAPOR PRESSURE @ 25°C:
 N/D
 VAPOR DENSITY:
 N/D

SOLUBILITY IN WATER: N/D pH: N/D

VOLATILE CONTENT: N/D

NOTE: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

SECTION 4 - FIRE AND EXPLOSION HAZARD

FLASH POINT (CLOSED CUP): N/A

AUTO-IGNITION: N/D

FLAMMABILITY LIMITS IN AIR: N/D

EXTINGUISHING MEDIA: Carbon Dioxide(CO2). Water. Water fog (or spray) Dry Chemical. Foam.

UNSUITABLE EXTINGUISHING MEDIA: None.

FIRE-FIGHTING PROCEDURES: Self contained breathing apparatus and protective clothing should be worn in fighting fires involving

chemicals. If large amount is involved, evacuate area.

UNUSUAL FIRE HAZARDS: None

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products:

Sulfur Oxides.

Carbon Oxides and traces of incompletely burned carbon compounds.

Silicon Dioxide. Iodine Compounds. Formaldehyde.

If container is an aerosol product: Treat as compressed gas: EXTINGUISHING MEDIA: CO₂, Dry Chemical, Water Fog.

SECTION 5 - REACTIVITY DATA

STABILITY: Stable.

CONDITIONS TO AVOID: None.

HAZARDOUS POLYMERIZATION: Will not occur.

MATERIALS TO AVOID: Oxidizing material can cause a reaction. Water, moisture, or humid air can cause hazardous vapors to form.

SECTION 6 - HEALTH HAZARD DATA

ACUTE SIGNS/EFFECTS OF OVEREXPOSURE:

INGESTION: May cause gastric distress.

SKIN CONTACT: Uncured product contact will irritate lips, gums, tongue and skin.

INHALATION: Causes mild respiratory irritation.

EYE CONTACT: Uncured product contact irritates eyes.

MEDICAL CONDITIONS AGGRAVATED: None known CHRONIC EFFECTS OF OVEREXPOSURE: None known

EMERGENCY FIRST AID PROCEDURES:

INGESTION: No first aid should be needed.

SKIN: To clean from skin, remove completely with a dry cloth or paper towel before washing with detergent and water. Get medical

attention if irritation develops.

INHALATION: Move to fresh air.

EYES: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention.

NOTE TO PHYSICIAN: None known.

TOXICITY: Refer to Product Information OTHER: None known LD_{50} **ACUTE ORAL:** >10,000 mg/kg AMES TEST: Unknown

ACUTE DERMAL: LD_{50} None found PRINCIPLE ROUTES OF EXPOSURE: EYES, INHALATION

ACUTE INHALATION None found. PRODUCTS/INGREDIENTS: None known LC_{50}

SECTION 7 - SPECIAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: Use in a well ventilated area.

PROTECTIVE GLOVES: Cloth gloves

EYE AND FACE PROTECTION: Safety glasses OTHER PROTECTIVE EQUIPMENT: None known VENTILATION: Use only in well ventilated area.

SECTION 8 - SPILL / LEAK / DISPOSAL PROCEDURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Wipe or soak up in an inert material and put in a container for disposal.

Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the

protective equipment section.

DISPOSAL METHOD: Disposal should be made in accordance with Federal, State, and Local Regulations.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/L - NOT LISTED REV 07/11/2011 BJM

SECTION 9 - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Avoid contact with skin and eyes. CAUTION! Wearers of contact lenses must not handle lenses until all sealant has been cleaned from fingertips; residual silicone will transfer to lenses and cause severe eye irritation.

Use mechanical ventilation to stay below TLV of 10 PPM acetic acid.

Uncured product contact irritates eyes. Uncured product contact irritates skin.

Use in a well ventilated area to prevent irritation by vapors.

ENGINEERING CONTROLS: Eye wash stations.

SECTION 10 - SHIPPING / REGULATORY CLASSIFICATION DATA

DOT SHIPPING NAME: None DOT HAZARD CLASS: None DOT LABEL(S): None EPA HAZARD CLASS: Eye irritant CPSC CLASSIFICATION: Eye irritant TRANSPORTATION CLASS: IMO None

RID (OCTI): None ADR (ECE): None

RAR (IATA): None

NEPA/HMIS CLASSIFICATION: FLAMMABILITY: 1 REACTIVITY: 0 HEALTH: 2

SECTION 11 - ADDITIONAL INFORMATION

ADDITIONAL INFORMATION: These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is made. The recommended handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/L — NOT LISTED REV 07/11/2011 BJM Page 3 of 3