

MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 · 888-567-2206 · www.chromate.com

FOR CHEMICAL EMERGENCY Call ChemTrec day/night: 1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: DRAIN OPENER - PROFESSIONAL STRENGTH		SUPPLIER'S NAME: CHROMATE INDUSTRIAL CORPORATION	
PRODUCT # : 74380		SUPPLIER'S ADDRESS: 5250-A Naiman Parkway, Solon, OH 44139	
PRODUCT TYPE: Alkaline Cleaner		EMERGENCY PHONE: 800-535-5053	
CHEMICAL FAMILY: Surfactant Blend		DOT SHIPPING NAME: Compound, Cleaning liquid (contains Sodium	
HAZARD RATING:		Hydroxide) 8, NA 1760, PG II	
HEALTH: 2	FLAMMABILITY: 0	DOT HAZARD CLASS: Corrosive	
REACTIVITY: 2	PERSONAL PROTECTION: B		

SECTION 2 – INGREDIENTS INFORMATION						
CHEMICAL NAME	CAS NO.	% / WT .	THRESHOLD LIMIT VALUE			
*SODIUM HYDROXIDE SOLUTION	1310-73-2	TO 40	2mg/m3			
WATER	7732-18-5	TO 60	NONE			

*An asterisk indicates the toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and

Community Right-to-Know Act of 1986 and 40 CFR 372:

	SECTION 3 – PHYSICAL DATA
BOILING RANGE (°F): 212-220°F	SPECIFIC GRAVITY: 1.3
VAPOR PRESSURE: N/D	VAPOR DENSITY: Same as Water
% VOLATILE: 80-82	pH: 14
SOLUBILITY IN WATER: Complete	EVAPORATION RATE: N/A

PHYSICAL DESCRIPTION: Clear Liquid, No Odor

SECTION 4 – REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will Not Occur

INCOMPATIBILITY (MATERIALS TO AVOID): None

HAZARDOUS DECOMPOSITION PRODUCTS: Normal products of combustion.

SECTION 5 – FIRE & EXPLOSION HAZARD DATA

FLASH POINT: Exceeds 200° F

FLAMMABILITY: Non-Flammable

EXTINGUISHING MEDIA: Water, CO2

SPECIAL FIRE-FIGHTING PROCEDURES: Floor may be slippery.

UNUSUAL AND EXPLOSION HAZARDS: None

	SECTION 6 – STOR	AGE AND HANDLING I	NFORMATION				
SPECIAL PRECAUTIONS:	PRECAUTIONS: Keep out of reach of children. Use only in well ventilated area.						
	For institutional and industrial	use only. For use by trained p	ersonnel only.				
	Store and keep in closed cont	ainer, in a cool place. Avoid free	ezing.				
SECTION 7 – HEALTH HAZARD DATA							
EYES: May cause irritation.		EXPOSURE LIMITS: N/E					
SKIN: May cause irritation.		INHALATION: May cause irritation to upper tract.					
INGESTION: May cause irritation of mucous membranes.							
MEDICAL CONDITION AGGRAVATED BY EXPOSURE: Person with present skin disorder may be more susceptible to irritation.							
CARCINOGENICITY:	NTP: N/L	IARC: N/L	OSHA: N/R				
SECTION 8 – FIRST AID PROCEDURE							

EYES: Flush with running water for 15 minutes.

SKIN: Wash off with soap and water.

INHALATION: Remove to fresh air.

INGESTION: Do not induce vomiting. Drink plenty of water. If unconscious or in convulsion, take to hospital or physician.

SECTION 9 - PRECAUTIONS FOR SAFE HANDLING

RESPIRATORY PROTECTION: No special requirements.

PROTECTIVE GLOVES: Chemical resistant.

VENTILATION: Good ventilation required.

EYE CONTACT: Goggles or Face Shield.

SECTION 10 - SPILL OR LEAK

SPILLAGE: Dike & contain spill, absorb the liquid.

DISPOSAL: Scoop or shovel solid material into a suitable container for recovery or disposal. Area may become slippery.

Flush cleaned area with water. Dispose according to local, state and federal requirements.

OTHER INFORMATION

THIS PRODUCT SAFETY DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATION SAFETY AND HEALTH.