

# **MATERIAL SAFETY DATA SHEET**

# CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

FOR CHEMICAL EMERGENCY

Call ChemTrec day/night: 1-800-424-9300

## PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SUPER IMPACT MOLY G GREASE DATE PREPARED: February 11, 2009

PART NUMBER: 74400 CHROMATE INDUSTRIAL CORPORATION

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

**DOT Hazard Classification: Non-Hazardous** 

NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA

#### **SECTION 1 – MATERIAL IDENTIFICATION AND INFORMATION**

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

NFPA RATING: Health: 1 Flammability: 1 Reactivity: 0 Special: --

HMIS RATING: Health: 1 Flammability: 1 Reactivity: 0 Personal Protection: B

COMPONENTS- CAS Number SARA OSHA PEL ACGIH CARCINOGEN CHEMICAL NAMES/COMMON NAMES III LIST (ppm) TLV (ppm) Ref. Source \*\*

(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)

PETROLEUM OIL MIXTURE 8002-05-9 No 5mg/M3 5mg/M3 d

TWA for oil TWA for oil mist mist

#### **SECTION 2 - PHYSICAL / CHEMICAL CHARACTERISTICS**

Boiling Point: N/A Specific Gravity (H2O=1): 0.8

Vapor Pressure: PSIG @ 70°F (Aerosols): N/A Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): <0.01

Vapor Density (Air = 1): 12 Evaporation Rate ( = 1): N/A

Solubility in Water: Negligible Water Reactive: No

Appearance and Odor: Dark green gel with oil odor.

## SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols): N/A

Auto-Ignition Temperature: N/A

Flammability Limits in Air by % in Volume: % LEL: N/D % UEL: N/D

FLASH POINT AN D METHOD USED (non-aerosols): >400°F COC

SPECIAL FIRE FIGHTING PROCEDURES: Self -contained breathing apparatus (SCUBA).

**EXTINGUISHER MEDIA:** Dry chemical (preferred), carbon dioxide, foam, water.

Unusual Fire & Explosion Hazards: Empty containers may retain product residue including flammable or explosive vapors. Do not cut, drill,

grind or weld on or near full, part full or empty drum.

#### **SECTION 4 – REACTIVITY HAZARD DATA**

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INCOMPATIBILITY (MATERIALS TO AVOID): Chlorine or oxygen.

CONDITIONS TO AVOID: Oxidizing atmospheres.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal: unidentified organics. Oxidation: oxides of carbon.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/R — NOT REGULATED N/L — NOT LISTED Page 1 of 2 REV 02/11/2009 BJM

#### **SECTION 5 - HEALTH HAZARD DATA**

PRIMARY ROUTES OF ENTRY: SKIN ABSORPTION

**ACUTE EFFECTS** 

Inhalation: Not expected to be a problem. Massive exposure to vapors or fumes may cause headaches, dizziness, and/or drowsiness.

**Eye Contact:** May cause irritation. **Skin Contact:** May cause irritation.

Ingestion: May cause vomiting, nausea, diarrhea.

CHRONIC EFFECTS: None noted.

Medical Conditions Generally Aggravated by Exposure: Dermatitis.

**EMERGENCY FIRST AID PROCEDURES** 

Eye Contact: Wash with large amounts of water. If irritation persists, call a physician.

**Skin Contact:** Remove contaminated clothing. Wash with soap and water.

Inhalation: Remove to fresh air.

Ingestion: DO NOT INDUCE VOMITING. Give 3-4 glasses of water. Seek medical attention.

#### **SECTION 6 – CONTROL AND PROTECTIVE MEASURES**

Respiratory Protection (specify type): None required.

Protective Gloves: Oil resistant types.

N/L - NOT LISTED

Eye Protection: Splash goggles or safety glasses.

Ventilation Requirements: None required in excess to normal ventilation.

Other Protective Clothing & Equipment: Oil resistant apron.

Hygienic Work Practices: Do not work in oil soaked clothing. Wash after handling.

## SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Stop flow, dike spill, eliminate all ignition sources, absorb on inert material

and scrape up.

Waste Disposal Methods: Dispose of in accordance with local, state and federal regulations.

Precautions To Be Taken In Handling & Storage: Avoid prolonged exposure to mist and vapors. Avoid flames, sparks and hot surfaces.

Keep containers closed. Shelf life one year.

Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Empty containers may contain explosive gas.

# OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/R — NOT REGULATED