

MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

FOR CHEMICAL EMERGENCY

Call ChemTrec day/night: 1-800-424-9300

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: DOUBLE/BUBBLE® EXTRA FAST SET DATE PREPARED: February 9, 2010

(NON-SAG) EPOXY (PARTS A & B) CHROMATE INDUSTRIAL CORPORATION

PART NUMBER: 74492 5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

PART A PART B

PRODUCT TYPE: EPOXY PRODUCT TYPE: MERCAPTAN-TERMINATED POLYMER HAZARD RATING: HEALTH: 2 FIRE: 1 REACTIVITY: 0 HAZARD RATING: HEALTH: 2 FIRE: 1 REACTIVITY: 0

PPI: N/L PPI: N/L

PART A — SECTION 2 — INGREDIENT / HAZARD INFORMATION

HAZARDOUS INGREDIENTSCAS NUMBEREPOXY RESIN25068-38-6AMORPHOUS SILICATRADE SECRETPOLYDIMETHYLSILOXANETRADE SECRET

SECTION 3 — HAZARDS IDENTIFICATION

EYE CONTACT: Product is moderately irritating to the eyes.

SKIN CONTACT: Product is moderately irritating to the skin. May cause skin sensitization. Skin sensitization may be evidenced by rashes,

especially hives.

INHALATION: Because of its low volatility this product is not likely to be an inhalation hazard.

INGESTION: This product is considered to have a low order of acute oral toxicity.

AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin and eye disorders may be aggravated by exposure to this product.

Pre-existing skin or lung allergies may increase the chance of developing increased allergy

symptoms from exposure to this product.

HEALTH HAZARD INFORMATION:

CARCINOGENICITY: The materials used in the manufacture of this product are not found on the OSHA, IARC or NTP lists of carcinogens.

OTHER HEALTH INFORMATION (EPOXY RESIN)

CHRONIC STUDIES: Recent 2 year bioassays in mice exposed by the dermal route to epoxy resin, the DIGLYCIDYL ETHER OF

BISPHENOL A (DGEBPA), or to resins predominantly of DGEBPA have yielded very limited evidence of weak carcinogenicity. DGEBPA is a component of the resin in this product. The authors of this work concluded that the renal tumor evidence with this resin "was of no biological significance" and that the resin "is not a systemic carcinogen when applied to the dorsal skin CF 1 mice." IARC concluded that DGEBPA was not classifiable as a carcinogen (IARC

GROUP 3), based on the following: HUMAN AND ANIMAL EVIDENCE BOTH INADEQUATE.

MUTAGENICITY: Both the resin and DGEBPA, have proven to be inactive when tested by in vivo mutagenicity assays. They have both

shown activity by the in vitro microbial mutagenicity screening and have both produced chromosomal aberrations in

cultured rat liver cells. The significance of this information to man is unknown.

SECTION 4 — FIRST AID MEASURES

EYE CONTACT: Flush eyes with plenty of water for 15 minutes while holding eyelids open. GET IMMEDIATE MEDICAL ATTENTION.

SKIN CONTACT: Remove contaminated clothing and wipe excess from skin. Flush skin with water. Follow by washing with soap and water.

If irritation occurs, get medical attention. Launder contaminated clothing. Destroy leather articles including shoes.

INHALATION: Remove person to fresh air and provide oxygen if breathing is difficult. GET MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ADVICE.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/R — NOT REGULATED N/L — NOT LISTED

^{***} ALL Ingredients in this product are listed in the T.S.C.A. Inventory

SECTION 5 — FIRE-FIGHTING MEASURES

FLAMMABILITY CLASS: IIIB FLASH RANGE: N/A

PENSKY-MARTENS CLOSED CUP ASTM D 93

375°F

EXPLOSIVE RANGE: N/A

FIRE-FIGHTING MEASURES: Water fog, dry chemical, foam, carbon dioxide.

> Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive-pressure, NIOSH-approved, self-contained breathing

apparatus (SCBA). Cool fire-exposed containers with water.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

SPILLS: Absorb liquid material and place in container for disposal. Comply with local, state and federal EPA Regulations.

SECTION 7 - HANDLING AND STORAGE

STORAGE CONDITIONS: Store in a cool, dry place. Keep away from open flames and high temperatures.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

	ACGIH ILV	ACGIH ILV-C	ACGIH STEL	OSHA STEL	OSHA PEL
EPOXY RESIN	N/E	N/E	N/E	N/E	N/E
AMORPHOUS SILICA	15.0000 mg/m ³	N/E	N/E	N/E	15.0000 mg/m ³
POLYDIMETHYLSILOXANE	N/E	N/E	N/E	N/E	N/E

PERSONAL PROTECTIVE EQUIPMENT: In the absence of proper environmental control or ventilation, wear a respirator approved

by NIOSH/MSHA whenever exposed to fumes or vapors. Comply with OSHA 1910.134 (CFR). Self-contained breathing apparatus in high concentrations. Local exhaust is recommended. Use chemical resistant protective gloves, chemical splash goggles, chemical resistant protective

clothing to minimize exposure, chemical splash apron, full face shield. Eye wash station and safety shower should be available for emergency use.

SECTION 9 - PHYSICAL / CHEMICAL PROPERTIES

FORM: Liquid APPEARANCE/COLOR: Bright Pink

BOILING RANGE: N/A ODOR: Mild VAPOR PRESSURE (mmHg): N/A **MELTING POINT:** N/A **EVAPORATION RATE: N/A** % VOLATILE: N/A

SPECIFIC GRAVITY: 1.19

SECTION 10 - STABILITY AND REACTIVITY

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur.

REACTIVITY

INCOMPATIBILITY: Oxidizing agents, strong mineral acids, strong lewis acids, bases, mercaptans, amines.

CONDITIONS TO AVOID: High temperatures.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, aldehydes, acids.

N/A — NOT APPLICABLE N/L - NOT LISTED 02/09/2010 BJM Page 2 of 6

SECTION 11 - TOXICOLOGICAL INFORMATION

LETHAL DOSE INFORMATION (PPM) ORAL SKIN INHALE LC₅₀

TOXICOLOGICAL INFORMATION: No information is available.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No information is available.

SECTION 13 - DISPOSAL CONSIDERATIONS

RCRA CONSIDERATIONS: This product, if disposed of in the purchased form, is not considered RCRA hazardous.

SECTION 14 - TRANSPORT INFORMATION

UN NUMBER:N/LUN PACK GROUP:N/LUN CLASS:N/LICAO/IATA CLASS:N/R

IMDG CLASS: N/R SHIPPING NAME: PLASTIC LIQUID, NOS

ADR/RID CLASS: N/R DOT HAZARD CLASS: N/L

TECHNICAL NAME: N/L

SECTION 15 - REGULATORY INFORMATION

TSCA STATUS: All ingredients contained in this product are on the TSCA Inventory.

INVENTORY STATUS: All component(s) of this product have been found on the following inventories:

UNITED STATES

All the component(s) of this product have NOT YET been identified on the following inventories:

EUROPE CANADA AUSTRALIA JAPAN KOREA CHINA PHILIPPINES

SCHEDULE B NUMBER: 3506.91.0000 is the Schedule B Export Classification Number.

PROPOSITION 65 INFORMATION: 74492 PART A contains chemicals known to the State of California to cause cancer/reproductive toxicity.

106-89-8 EPICHLOROHYDRIN <1 ppm 122-60-1 PHENYL GLYCIDYL ETHER <6 ppm

SECTION 16 - OTHER INFORMATION

DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter known as, "Information") are presented in good faith and believed to be correct, as of the date hereof, Chromate Industrial Corporation (hereinafter known as, "CIC") makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will CIC be responsible for damages of any nature whatsoever resulting from the use of, or reliance upon, information. No representations, or warranties, either expressed or implied, or merchantability, fitness for a particular purpose of any nature are made hereunder with respect to information or the product to which information refers.

N/L — NOT LISTED

Page 3 of 6

02/09/2010 BJM

PART B — SECTION 2 — INGREDIENT / HAZARD INFORMATION

HAZARDOUS INGREDIENTS CAS NUMBER MERCAPTAN TERMINATED POLYMER TRADE SECRET **TERTIARY AMINE** TRADE SECRET AMORPHOUS SILICA TRADE SECRET POLYDIMETHYLSILOXANE TRADE SECRET

SECTION 3 — HAZARDS IDENTIFICATION

EYE CONTACT: Corrosive to the eyes and may cause severe damage including blindness. Vapors may be irritating. SKIN CONTACT: May cause severe skin irritation. Corrosive on prolonged contact. Slightly toxic by skin absorption.

Slightly toxic. Can cause irritation of respiratory tract. Over-exposure to vapor or fumes may cause delayed lung damage INHALATION:

chemical pneumonia.

INGESTION: Slightly toxic. Ingestion may cause fatigue, muscular weakness, labored breathing and irritation of gastrointestinal tract. NOTES TO PHYSICIAN:

Gastric lavage may be considered depending on degree of mucosal damage. Treatment of shock, respiratory

depression and convulsions may be necessary.

OVER-EXPOSURE HEALTH HAZARD INFORMATION

ACUTE: Severe burns to skin, eyes, respiratory and gastrointestinal tracts.

CHRONIC: Dermatitis, delayed lung injury, chemical pneumonia.

HEALTH HAZARD INFORMATION

CARCINOGENICITY: The materials used in the manufacture of this product are not found on the OSHA, IARC OR NTP lists of carcinogens.

SECTION 4 — FIRST AID MEASURES

EYE CONTACT: Flush thoroughly with water for at least 15 minutes, while lifting upper and lower eye lids.

GET IMMEDIATE MEDICAL ATTENTION.

SKIN CONTACT: Wipe excess from skin and flush with water for at least 15 minutes. GET MEDICAL ATTENTION.

Launder clothing, discard leather clothing.

INHALATION: Remove person to fresh air and call a physician. Prevent aspiration of vomit by turning victims head to the side. INGESTION: DO NOT INDUCE VOMITING. Administer 3-4 glasses of milk or water. GET IMMEDIATE MEDICAL ATTENTION.

Nothing by mouth if victim is drowsy, convulsing or unconscious.

SECTION 5 — FIRE-FIGHTING MEASURES

FLAMMABILITY CLASS: IIIB FLASH RANGE:

Pensky-Martens Closed Cup ASTM D 93

270°F

EXPLOSIVE RANGE: N/A

FIRE-FIGHTING MEASURES: Water fog, dry chemical, foam, carbon dioxide.

> Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive-pressure, NIOSH-approved, self-contained breathing

apparatus (SCBA). Cool fire-exposed containers with water.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

SPILLS: Absorb liquid material and place in container for disposal. Comply with local, state and federal EPA Regulations.

SECTION 7 - HANDLING AND STORAGE

STORAGE CONDITIONS: Store in a cool, dry place. Keep away from open flames and high temperatures.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/L - NOT LISTED 02/09/2010 BJM

^{***} ALL Ingredients in this product are listed in the T.S.C.A. Inventory

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
MERCAPTAN TERMINATED POLYMER	N/E	N/E	N/E	N/E	N/E
TERTIARY AMINE	N/E	N/E	N/E	N/E	N/E
AMORPHOUS SILICA	15.0000 mg/m ³	N/E	N/E	N/E	15.0000 mg/m ³
POLYDIMETHYLSILOXANE	N/E	N/E	N/E	N/E	N/E

PERSONAL PROTECTIVE EQUIPMENT: In the absence of proper environmental control or ventilation, wear a respirator approved

by NIOSH/MSHA whenever exposed to fumes or vapors. Comply with OSHA 1910.134 (CFR). Self-contained breathing apparatus in high concentrations. Local exhaust is recommended. Use chemical resistant protective gloves, chemical splash goggles, chemical resistant protective

clothing to minimize exposure, chemical splash apron, full face shield. Eye wash station and safety shower should be available for emergency use.

SECTION 9 - PHYSICAL / CHEMICAL PROPERTIES

FORM: Liquid APPEARANCE/COLOR: Off-white

ODOR:MercaptanBOILING RANGE:N/AVAPOR PRESSURE (mmHg):N/AMELTING POINT:N/AEVAPORATION RATE:N/A% VOLATILE:N/A

SPECIFIC GRAVITY: 1.15

SECTION 10 - STABILITY AND REACTIVITY

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur.

REACTIVITY

INCOMPATIBILITY: Oxidizing agents, cleaning solutions, strong mineral and lewis acids, halogenated organic compounds.

CONDITIONS TO AVOID: High temperatures.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, nitrogen oxides, ammonia, hydrogen sulfide,

oxides of sulfur.

SECTION 11 - TOXICOLOGICAL INFORMATION

LETHAL DOSE INFORMATION (PPM) ORAL SKIN INHALE LC₅₀

TOXICOLOGICAL INFORMATION: No information is available.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No information is available.

SECTION 13 - DISPOSAL CONSIDERATIONS

RCRA CONSIDERATIONS: This product, if disposed of in the purchased form, is not considered RCRA hazardous.

SECTION 14 - TRANSPORT INFORMATION

IMDG CLASS: N/R SHIPPING NAME: PLASTIC LIQUID, NOS

ADR/RID CLASS: N/R DOT HAZARD CLASS: N/L

TECHNICAL NAME: N/L

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/R — NOT REGULATED N/L — NOT LISTED Page 5 of 6 02/09/2010 BJM

SECTION 15 - REGULATORY INFORMATION

TSCA STATUS: All ingredients contained in this product are on the TSCA Inventory.

INVENTORY STATUS: All component(s) of this product have been found on the following inventories:

UNITED STATES

All the component(s) of this product have NOT YET been identified on the following inventories:

EUROPE
CANADA
AUSTRALIA
JAPAN
KOREA
CHINA
PHILIPPINES

SCHEDULE B NUMBER: 3506.91.0000 is the Schedule B Export Classification Number.

PROPOSITION 65 INFORMATION: 74492 PART A does not contain chemicals known to the State of California to cause

cancer/reproductive toxicity.

SECTION 16 – OTHER INFORMATION

DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter known as, "Information") are presented in good faith and believed to be correct, as of the date hereof, Chromate Industrial Corporation (hereinafter known as, "CIC") makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will CIC be responsible for damages of any nature whatsoever resulting from the use of, or reliance upon, information. No representations, or warranties, either expressed or implied, or merchantability, fitness for a particular purpose of any nature are made hereunder with respect to information or the product to which information refers.