

MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 · 888-567-2206 · www.chromate.com

FOR CHEMICAL EMERGENCY Call ChemTrec day/night: 1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED LION E-Z POXY AQUAMEND PART NUMBER: 74500

DATE PREPARED: March 17, 2009

CHROMATE INDUSTRIAL CORPORATION

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 2 - COMPONENTS / INGREDIENTS INFORMATION

| COMPONENT/EXPOSURE LIMITS | | CAS# | % BY WT. |
|---|----------------------|------------|-----------|
| DIGYLCIDYL ETHER OF BISPHENOL A INGESTION LD _{so} : >5000 mg/kg (rat) | | 25085-99-8 | 7% to 13% |
| SKIN ABSORPTION: 20000 mg/kg (rabbit) | | | |
| NOVOLAC EPOXY RESIN | | 28064-14-4 | 3% to 7% |
| ORAL LD ₅₀ : | >2000 mg/kg (Rat) | | |
| SKIN ABS LD ₅₀ : | >2000 mg/kg (Rabbit) | | |
| SENSITIZATION SKIN: Has caused allergic skin reactions in guinea pigs. | | | |
| POLYMERIC PHENOLIC AMINE | | 32610-77-8 | 1% to 5% |
| ORAL LD ₅₀ : | 2200 mg/kg (rat) | | |
| INHALATION LC ₅₀ 1 hr: >20 mg/l (rat) | | | |
| SKIN: Moderate skin irriation. | | | |

SECTION 3 – HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYE: May cause moderate eye irritation.

SKIN: Has caused allergic skin reactions in humans. A single exposure not likely to cause skin irritation. Prolonged and repeated contact may cause skin irritation with local redness.

INGESTION: Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

INHALATION: Vapors are unlikely due to physical properties.

CHRONIC (CANCER) INFORMATION: N/A TERATOLOGY (BIRTH DEFECT) INFORMATION: N/A REPRODUCTION INFORMATION: N/A

SECTION 4 – FIRST AID MEASURES

EYES: Flush eyes thoroughly with water for several minutes. If effects occur, consult a physician, preferably an opthalmologist. **SKIN:** Wash skin with plenty of soap and water.

INGESTION: No emergency medical treatment necessary.

INHALATION: N/A

NOTE TO PHYSICIANS: Consider additional thorough skin wash with mild, nonabrasive soap and plenty of warm water for at least 15 minutes.

SECTION 5 – FIRE-FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: > 140°F

Method: N/A

FLAMMABLE LIMITS: LOWER FLAMMABLE LIMIT (LEL): N/A UPPER FLAMMABLE LIMIT (UEL): N/A

AUTO-IGNITION TEMPERATURE: N/A

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, carbon monoxide, oxides of nitrogen and sulfur.

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

FIREFIGHTING INSTRUCTIONS: Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool. Fire Fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protective clothing.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

SPILLS: Dispose of in normal manner in accordance to all applicable state, federal, and local laws. Not a hazardous waste.

SECTION 7 – HANDLING AND STORAGE

HANDLING: No special precautions needed.

Personal Hygiene: Wash thoroughly after handling, especially before eating, drinking, smoking, and using restroom facilities. Professionally launder contaminated clothing before use.

Empty Container Precautions: Do not reuse empty containers for food, clothing, or products for human or animal consumption, or where skin contact can occur.

STORAGE:

Temperature: < 90°F.

Conditions: Store in cool, dry, well-ventilated area.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

Local Exhaust: Use to keep exposures below recommendations. Use if material is heated above 100°F. **RESPIRATORY PROTECTION:** None required in a well-ventilated area.

SKIN PROTECTION: Appropriate impervious gloves. Because a variety of protective gloves exist, consult glove manufacturer to determine the proper type for the specific operation.

EYE PROTECTION: Safety glasses or goggles.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 446°F / 230°C VAPOR PRESSURE: N/A SOLUBILITY IN WATER: Insoluble in water pH: N/A ODOR: Mercaptan/sulfur MELTING POINT: N/A VAPOR DENSITY: N/A SPECIFIC GRAVITY: 1.97201 VOLATILE ORGANIC COMPOUNDS: <0.1% APPEARANCE: Putty

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY (CONDITIONS TO AVOID): This product is stable. INCOMPATIBILITY: None. HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, aldehydes, acids, oxides of sulfur and nitrogen HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11 — TOXICOLOGICAL INFORMATION

EYE: N/A INGESTION: N/A

SUBCHRONIC: N/A CHRONIC/CARCINOGENICITY: N/A REPRODUCTION: N/A SKIN: N/A INHALATION: N/A

TERATOLOGY: N/A MUTAGENICITY: N/A

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: N/A CHEMICAL FATE INFORMATION: N/A

SECTION 13 — DISPOSAL CONSIDERATIONS

Incinerate in furnace or bury in landfill in accordance with all applicable regulations. Not classified as a hazardous waste.

SECTION 14 — TRANSORT INFORMATION

Not DOT regulated.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS
TSCA: All ingredients are TSCA listed.
OSHA: Not OSHA regulated.
CERCLA: SARA HAZARD CATEGORY: Not regulated.
SECTION 313: Not regulated.

INTERNATIONAL REGULATIONS CANADIAN WHMIS: DB2 skin sensitizer. CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA): N/A EINECS: EINECS listed.

STATE REGULATIONS

CALIFORNIA PROPOSITION 65: This product contains the following chemicals known to the state of California to cause cancer or reproductive toxicity: *None*

The following ingredients are present in this material and are subject to reporting in accordance to the Pennsylvania, New Jersey, and/or Massachusetts Right-to-Know (RTK) laws:

MAGNESIUM SILICATE HYDRATE (CAS:14807-96-6)

POLYETHER POLYMERCAPTAN (TRADE SECRET)

SODIUM CALCIUM MAGNESIUM SILICATE (CAS:65997-17-3)

SECTION 16 — OTHER INFORMATION

HAZARD RATINGS

NFPA RATINGS: HEALTH: 1

FIRE: 0

PHYSICAL DATA: 0

PPE: B

User has the responsibility to provide a safe workplace, all aspects on an individual operation should be examined to determined if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information herein should be passed on to your customers or employees as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damage incurred by the use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representation of warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information refers. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.