

MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 · 888-567-2206 · www.chromate.com

FOR CHEMICAL EMERGENCY Call ChemTrec day/night: 1-800-424-9300

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: INSTANT ADHESIVE GEL

DATE PREPARED: JULY 11, 2011

PART NUMBER: 74516

CHROMATE INDUSTRIAL CORPORATION

PRODUCT TYPE: CYANOACRYLATE

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 2 — HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS: HEALTH: 2	FLAMMABILITY: 2		PHYSICAL HAZARD: 1	PERSONAL PRO	TECTION: See Section 8
PHYSICAL STATE	: Liquid	COLOR:	Clear, colorless, Straw	ODOR:	Sharp, Irritating
WARNING:	BONDS SKIN IN SECONDS. COMBUSTIBLE LIQUID AND MAY CAUSE EYE and RESPI		TRACT IRRITATION.		

RELEVANT ROUTES OF EXPOSURE: SKIN, INHALATION, and EYES

POTENTIAL HEALTH EFFECTS

INHALATION: Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest.

SKIN CONTACT: Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin. Bonds sikin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare.

- **EYE CONTACT:** Irritating to the eyes. Causes excessive tearing. Eyelids may bond.
- **INGESTION:** Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.

EXISTING CONDITIONS AGGRAVATED BY EXPOSURE: EYE, SKIN, and RESPIRATORY DISORDERS.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). See Section 11 for additional toxicological information.

SECTION 3 — COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS ETHYL 2-CYANOACRYLATE THICKENER CAS NUMBER 7085-85-0 PROPRIETARY **%** 60 - 100

1 - 5

	SECTION 4 — FIRST AID MEASURES			
INHALATION: SKIN CONTACT:	Move to fresh air. If symptoms persist, seek medical advice. Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned du to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips an encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.			
EYE CONTACT:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized Cyanoacrylate trapped behind the eyelid caused abrasive damage.			
INGESTION:	Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.			
NOTES TO PHYS	ICIAN: Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.			

SECTION 5 — FIRE-FIGHTING MEASURES

FLASH POINT: 80 - 93.3°C (176°F - 199.94°F) Tagliabue Closed Cup					
AUTO-IGNITION TEMPERATURE: 485°C (905°F)					
FLAMMABLE/EXPLOSIVE LIMITS LOWER: N	N/D UPPER: N/D				
EXTINGUISHING MEDIA: Foam. Carbon Dioxide. Dry powder.					
SPECIAL FIRE-FIGHTING PROCEDURES: V	Wear a self-contained breathing apparatus with a full face piece operated in pressure-				
d	demand or other positive pressure mode.				
UNUSUAL FIRE OR EXPLOSION HAZARDS: None.					
HAZARDOUS COMBUSTION PRODUCTS:	Frace amounts of toxic and/or irritating fumes may be released and the use of breathing				
а	apparatus is recommended.				

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

ENVIRONMENTAL PRECAUTIONS: Ventilate area. Do not allow product to enter sewer or waterways.

CLEAN-UP METHODS: Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

SECTION 7 — HANDLING AND STORAGE

- **HANDLING:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.
- **STORAGE:** Keep in a cool, well-ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready to use.

SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

HAZARDOUS COMPONENTS	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
ETHYL 2-CYANOACRYLATE	0.2 PPM TWA	None	None	None
THICKENER	None	None	None	None

ENGINEERING CONTROLS: Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

RESPIRATORY PROTECTION: Use NIOSH-approved respirator if there is potential to exceed exposure limit(s).

EYE/FACE PROTECTION: Safety goggles or safety glasses with side shields.

SKIN PROTECTION: Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon, or cotton.

SECTION 9 — PHYSICAL / CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid **ODOR:** Sharp, Irritating pH: Not applicable BOILING POINT/RANGE: > 300°F (> 148.9°C) none SPECIFIC GRAVITY: 1.05 @ 75°F (23.89°C) FLASH POINT: 80 - 93.3°C (176°F - 199.94°F) Tagliabue Closed Cup FLAMMABLE/EXPLOSIVE LIMITS AUTO-IGNITION TEMPERATURE: 485 °C (905°F) EVAPORATION RATE: Not available PARTITION COEFFICIENT (N-OCTANOL/WATER): Not available

COLOR: Clear, colorless, Straw ODOR THRESHOLD: 1 - 2 ppm VAPOR PRESSURE: < 0.2 mm hg MELTING POINT/ RANGE: N/D VAPOR DENSITY: 3 Approximately

LOWER: Not available UPPER: Not available

OSHA CARCINOGEN (Specifically Regulated)

No

No

SOLUBILITY IN WATER: Polymerizes in presence of water. VOC CONTENT: <2%; <20 g/l (California SCAQMD Method 316B)

(Estimated)

SECTION 10 — STABILITY AND REACTIVITY

STABILITY: Stable under recommended storage conditions.

HAZARDOUS REACTIONS: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis, and alcohols. HAZARDOUS DECOMPOSITION PRODUCTS: None.

NTP CARCINOGEN

No

No

INCOMPATIBLE MATERIALS: Water, amines, alkalis, and alcohols.

CONDITIONS TO AVOID: Spontaneous polymerization.

SECTION 11 — TOXICOLOGICAL INFORMATION

ACUTE ORAL PRODUCT TOXICITY: ACUTE DERMAL PRODUCT TOXICITY: LD₅₀ (rat) > 5,000 mg/kg (Estimated) LD₅₀ (rabbit) > 2,000 mg/kg (Estimated)

HAZARDOUS	COMPONENTS

ETHYL 2-CYANOACRYLATE THICKENER

HAZARDOUS COMPONENTS

ETHYL 2-CYANOACRYLATE

THICKENER

HEALTH EFFECTS/TARGET ORGANS

IARC CARCINOGEN

Irritant, Allergen, Respiratory

No

No

Irritant

SECTION 12 — ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Not available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Information provided is for unused product only. **RECOMMENDED METHOD OF DISPOSAL:** Follow all local, State, Federal and Provincial regulations for disposal. **HAZARDOUS WASTE NUMBER:** Not a RCRA hazardous waste.

SECTION 14 — TRANSPORTATION INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION GROUND (49 CFR) PROPER SHIPPING NAME: COMBUSTIBLE LIQUID, NOS (CYANOACRYLATE ESTER) HAZARD CLASS OR DIVISION: COMBUSTIBLE LIQUID PACKING GROUP: III EXCEPTIONS: UNIT

IDENTIFICATION NUMBER: NA 1993 EXCEPTIONS: UNRESTRICTED, (NOT MORE THAN 450 LITERS)

INTERNATIONAL AIR TRANSPORTATION (ICAO/IATA) PROPER SHIPPING NAME: AVIATION REGULATED LIQUID, NOS (CYANOACRYLATE ESTER) HAZARD CLASS OR DIVISION: 9 IDENTIFICATION NUMBER:

IDENTIFICATION NUMBER: UN 3334 **EXCEPTIONS:** (Not more than 500 ml) Unrestricted

WATER TRANSPORTATION (IMO/IMDG)

PACKING GROUP: None

PROPER SHIPPING NAME: Not Regulated IDENTIFICATION NUMBER: None

HAZARD CLASS OR DIVISION: None PACKING GROUP: None

SECTION 15 — REGULATORY INFORMATION

UNITED STATES REGULATORY INFORMATION

TSCA 8 (B) INVENTORY STATUS: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. TSCA 12(B) EXPORT NOTIFICATION: None above reporting de minimus.

CERCLA/SARA SECTION 302 EHS: None above reporting de minimus.

CERCLA/SARA SECTION 311/312: Immediate Health, Delayed Health, Fire, Reactive.

CERCLA/SARA 313: None above reporting de minimus.

CALIFORNIA PROPOSITION 65: No California Proposition 65 listed chemicals are known to be present.

CANADA REGULATORY INFORMATION

CEPA DSL/NDSL STATUS: All components are listed on or are exempt from listing on the Canadian Domestic Substance List. **WHMIS HAZARD CLASS:** B.3, D.2.B

SECTION 16 — OTHER INFORMATION

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Chromate Industrial Corporation (CIC) does not assume responsibility for any results obtained by persons over whose methods CIC has no control. It is the user's responsibility to determine the suitability of CIC's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of CIC's products. In light of the foregoing, CIC specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of CIC's products. CIC further disclaims any liability for consequential or incidental damages of any kind, including lost profits.