

# MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 · 888-567-2206 · www.chromate.com

FOR CHEMICAL EMERGENCY Call ChemTrec day/night: 1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED LION RAPID SEAL PART NUMBER: 74572 DATE PREPARED: April 14, 2009

#### CHROMATE INDUSTRIAL CORPORATION

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

#### SECTION 2 - COMPOSITION / DATA ON COMPONENTS

**CHEMICAL DESCRIPTION:** This product is a mixture of the substances listed below with nonhazardous additions. **DANGEROUS COMPONENTS:** 

1317-65-3	
108-88-3	
8052-42-4	
64742-89-8	
14807-96-6	
1332-58-7	
74-98-6	
106-97-8	

CALCIUM CARBONATE	31.28%
TOLUENE	18.23%
ASPHALT	15.3%
VM&P NAPTHA	11.7%
TALC (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	7.2%
ALUMINUM SILICATE	6.3%
PROPANE	6.3%
N-BUTANE	3.7%

#### SECTION 3 – HAZARDS IDENTIFICATION

 HAZARD DESCRIPTION:
 HARMFUL; EXTREMELY FLAMMABLE

 PHYSICAL DANGERS:
 EXTREMELY FLAMMABLE.

 IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

 HARMFUL: Danger of serious damage to health by prolonged exposure through inhalation.

 KEEP OUT OF THE REACH OF CHILDREN.

 EFFECTS OF CHRONIC OVEREXPOSURE: May cause permanent brain and nervous system damage. Repeated overexposure can also

damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA RATINGS (SCALE 0 - 4): HEALTH:	1	FIRE: 4	REACTIVITY: 3
HMIS-RATINGS (SCALE 0 - 4): HEALTH:	1	FIRE: 4	PHYSICAL HAZARD: 3

## SECTION 4 - FIRST AID MEASURES

**INHALATION:** Supply fresh air; consult doctor in case of complaints.

**SKIN CONTACT:** Immediately wash with water and soap and rinse thoroughly.

**EYE CONTACT:** Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. **INGESTION:** Contact physician or poison control center.

# SECTION 5 – FIRE-FIGHTING MEASURE

**EXTINGUISHING AGENTS:** CO<sub>2</sub>, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam. **PROTECTIVE EQUIPMENT:** No special measures required.

# SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL SAFETY PRECAUTIONS: Wear protective equipment. Keep unprotected persons away. ENVIRONMENTAL SAFETY PRECAUTIONS: Do not allow product to reach sewage systems or ground water. MEASURES FOR CLEANING/COLLECTING: Ensure adequate ventilation.

# SECTION 7 - HANDLING AND STORAGE

FIRE/EXPLOSION PROTECTION: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

STORAGE REQUIREMENTS: Observe pressurized container storage regulations. Consult with your local authorities.

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

COMPONENT	S WITH LIMIT	VALUES THAT REQUIRE MONITORING AT THE WORKPLACE:				
108-88-3	TOLUEN	NE				
	PEL Short-term value: C 300; 500* ppm					
		Long-term value: 200 ppm				
		*10-min peak per 8-hr shift				
	REL	Short-term value: 560 mg/m³, 150 ppm				
		Long-term value: 375 mg/m³, 100 ppm				
	TLV	75 mg/m³, 20 ppm				
8052-42-4	ASPHA	ASPHALT				
	REL	Short-term value: C 5* mg/m³				
		*15-min				
	TLV	0.5 l mg/m³				
		as benzene-soluble aerosol				
1332-58-7	ALUMIN	ALUMINUM SILICATE				
	PEL	15* 5** mg/m³				
		*total dust **respirable fraction				
	REL	10* 5** mg/m³				
		*total dust **respirable fraction				
	TLV	2* mg/m³				
		E; as respirable fraction				
74-98-6	PROPA	NE				
	PEL	1800 mg/m³, 1000 ppm				
	REL	1800 mg/m³, 1000 ppm				
	TLV	Varies mg/m <sup>3</sup> , 1000 ppm				
106-97-8	N-BUTA	NE				
	REL	1900 mg/m³, 800 ppm				
	TLV	Varies mg/m <sup>3</sup> , 1000 ppm				
PROTECTIVE	HYGIENIC M	EASURES: Keep away from foodstuffs and animal feed. Wash hands after use.				
		A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where				
		short and/or long term overexposure exists, a charcoal filter respirator should be worn. Please consult an				
		authority on chemical hygiene monitoring if you suspect overexposure conditions exist and need a specific				
		recommendation on proper ventilation techniques and personal protection.				
PROTECTION OF HANDS:		Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove				
		recommendation can be given.				
EYE PROTEC	TION: Tiahtly :	sealed goggles.				

EYE PROTECTION: Tightly sealed goggles.

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

**GENERAL INFORMATION: ODOR:** Aromatic FLASH POINT: -19°C AUTO IGNITING: Product is not self-igniting. DANGER OF EXPLOSION: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120°F. In use, may form flammable/explosive vapor-air mixture. LOWER EXPLOSION LIMIT: 0.9 Vol %

VAPOR PRESSURE: 40 PSI, 2750 hPa

SPECIFIC GRAVITY: Between 0.77 and 0.85 (Water equals 1.00) VOC CONTENT (LESS EXEMPT SOLVENTS): 39.9 % **MIR VALUE: 0.99** 

BOILING POINT/BOILING RANGE: -44°C **IGNITION TEMPERATURE: 470°C** 

UPPER EXPLOSION LIMIT: 10.2 Vol % DENSITY AT 20°C: 1.07089 g/cm3 VOC CONTENT: 427.5 g/l / 3.57 lb/gl **MIR VALUE: 39.9 %** SOLIDS CONTENT: 60.1 %

#### SECTION 10 - STABILITY AND REACTIVITY DATA

CONDITIONS TO BE AVOIDED: Do not allow the can to exceed 120°F. Stable at normal temperatures. POSSIBILITY OF HAZARDOUS REACTIONS: No dangerous reactions known.

#### SECTION 11 - TOXICOLOGICAL INFORMATION

PRIMARY EFFECT ON THE SKIN: Irritant to skin and mucous membranes.

PRIMARY EFFECT ON THE EYE: Irritating effect.

SENSITIZATION: No sensitizing effects known.

ADDITIONAL TOXICOLOGICAL INFORMATION: The product shows the following dangers according to internally approved calculation methods for preparations:

#### **SECTION 12 – ECOLOGICAL INFORMATION**

**OTHER INFORMATION:** This product does not contain any chloroflourocarbons (CFC's), chlorinated solvents, lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), or polybrominated diphenyl ether (PDBE). No specific ecological data is available for this product. ACQUATIC TOXICITY:

Hazardous for water, do not empty into drains.

#### SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. **RECOMMENDATION:** Completely empty cans should be recycled.

### **SECTION 14 – TRANSPORT INFORMATION**

HAZARD CLASS: 2.1 LABEL: 21 **UN-NUMBER: 1950** PACKAGING GROUP: || MARINE POLLUTANT: No PROPER SHIPPING NAME: AEROSOLS, FLAMMABLE Consumer Commodity ORM-D **IDENTIFICATION NUMBER: N/A** ADR/RID CLASS: 2 5F Gases IMDG CLASS: 2.1 EMS NUMBER: F-D.S-U ICAO/IATA CLASS: 2.1

SECTION 15 – REGULATIONS								
SARA SECTION 355 (EXTREMELY HAZARDOUS SUBSTANCES): None of the ingredients in this product are listed. SARA SECTION 313 (SPECIFIC TOXIC CHEMICAL LISTINGS): 108-88-3 TOLUENE								
TSCA (TOXIC SUBSTANCES CONTROL ACT): All ingredients are listed. PROPOSITION 65 CHEMICALS KNOWN TO CAUSE CANCER: None of the ingredients in this product are listed. PROPOSITION 65 CHEMICALS KNOWN TO CAUSE DEVELOPMENTAL TOXICITY: 108-88-3 TOLUENE								
EPA:	EPA: A: Known human carcinogen B: Proba		B: Probable hum	an carcinogen				
	C: Poss	sible huma	n carcinogen	D: Not classifiabl	e as to human carcinogenicity:			
				Inadequate h	uman and animal evidence of carcinogenicity (or no data is available).			
	108-88-	3	TOLUENE		II			
IARC:	Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.							
108-88-3		-	TOLUENE		3			
8052-42-4			ASPHALT		3			
	14807-9	90-0	TALC (Mg <sub>3</sub> H <sub>2</sub> (	SIO <sub>3</sub> ) <sub>4</sub> )	3			
ACGIH TLVs: A1-designates a confirmed human ca A2-designates a suspected human c A3-designates an animal carcinogen		ed human carcinogen.						
	A4-designates "not classifiable as a human carci		-	inogen".				
		108-88-3	B TOLI	JENE	A4			
		8052-42	-4 ASPI	HALT	A4			
		14807-9	6-6 TALC	C (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4			
		1332-58	-7 ALUI	MINUM SILICATE	A4			
NIOSH:	NIOSH: 8052-42-4 ASPHALT							
HAZARD SYMBOLS: HARMFUL, EXTREMELY FLAMMABLE HAZARD-DETERMINING COMPONENTS OF LABELLING: TOLUENE								

RISK PHRASES: EXTREMELY FLAMMABLE. IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

HARMFUL: Danger of serious damage to health by prolonged exposure through inhalation.

SAFETY PHRASES: KEEP OUT OF THE REACH OF CHILDREN. Keep in a cool place. Keep container in a well-ventilated place.

Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapor/spray. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas.

SPECIAL LABELING OF CERTAIN PREPARATIONS: KEEP OUT OF THE REACH OF CHILDREN.

## SECTION 16 – OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Page 4 of 4

#### ABBREVIATIONS AND ACRONYMS:

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

*EINECS:* European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

VOC: Volatile Organic Compounds (USA, EU)