

SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

1. IDENTIFICATION			
PRODUCT NAME: Red Lion Gasket & Paint Rem	nover DATE PREPARED: June 8, 2015		
PART NUMBER: 74113	MANUFACTURER: CHROMATE INDUSTRIAL CORPORATION 5250-A Naiman Parkway, Solon, OH 44139 • www.chromate.com		
RECOMMENDED USE: Not available.	EMERGENCY TELEPHONE NUMBER OF THE COMPANY: (888) 567-2206		
RECOMMENDED RESTRICTIONS: None known	PRODUCT INFORMATION TELEPHONE NUMBER: (888) 567-2206		
	. REGULATORY INFORMATION TELEPHONE NUMBER: (888) 567-2206		
	TRANSPORTATION EMERGENCY TELEPHONE NUMBER: (800) 424-9300		
	NATIONAL POISON CENTER: (800) 222-1222		
	2. HAZARDS IDENTIFICATION		
Physical hazards: Flammable aerosls - Category 1			
	Gases under pressure - Compressed gas		
	Skin corrosion/irritation - Category 2		
	Serious eye damage/eye irritation - Category 2A		
	Germ cell mutagenicity - Category 1B		
Carcinogenicity - Category 1B			
Specific target organ toxicity, repeated exposure - Category 1			
Environmental hazards:	Not classified.		

Not classified.

OSHA defined hazards:





Signal word: Hazard statements: Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statements:

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breath gas. Was thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

FOR CHEMICAL EMERGENCY

Call ChemTrec day/night:

1-800-424-9300

2. HAZARDS IDENTIFICATION CONTINUED		
Response:	If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before use.	
Storage:	Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified: Supplemental information:	None known. None.	

None.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methylene Chloride		75-09-2	60 - 80
Isobutane		75-28-5	2.5 - 10
Isopropyl Alcohol		67-63-0	2.5 - 10
Propane		74-98-6	2.5 - 10
Monoethanolamine		141-43-5	1 - 2.5
Anhydrous Ammonia		7664-41-7	0.1 - 1
Mineral Spirits		8052-41-3	0.1 - 1
Other components below reportable levels			2.5 - 10

*Designated that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4 FIRST-AID MEASURES

Inhalation:	Move to fresh air. Call a physician if symptoms develop or persisit.
Skin contact:	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact:	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion:	Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed: Dizziness. Nausea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Suitable extinguishing media:	Not available.
Unsuitable extinguishing media:	None known.
Specific hazards arising from the chemical:	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and	Firefighters must use standard protective equipment including flame retardant coat, helmet
precautions for fire fighters:	with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions:	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been
	exposed to heat. Move containers from fire area if you can do so without risk. Containers
	should be cooled with water to prevent vapor pressure build up. For massive fire in cargo
	area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire
	burn out.
Specific methods:	Use standard firefighting procedures and consider the hazards of other involved materials.
	Move container from fire area if you can do so without risk. Cool containers exposed to
	flames with water until well after the fire is out. In the event of fire and/or explosion do not
	breath fumes.
General fire hazards:	Extremely flammable aerosol.

5. FIRE-FIGHTING MEASURES

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breath gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up: Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. For waste disposal, see section 13 of the SDS.

Environmental precautions: Avoid discharge into drains, water courses or onto the ground.

7. HANDLING AND STORAGE

Precautions for safe handling: Obtain special intructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breath gas. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Level 1 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits:

US. OSHA Specifically Regu	lated Substances (29 CFR 1910.1001	-1050)	
Components	CAS Number	Туре	Value
Methylene Chloride	75-09-2	STEL	125 ppm
		TWA	25 ppm
US. OSHA Table Z-1 Limits f	or Air Contaminants (29 CFR 1910.10	000)	
Components	CAS Number	Туре	Value
Anhydrous Ammonia	7664-41-7	PEL	35 mg/m ³
Isopropyl Alcohol	67-63-0	PEL	50 ppm 980 mg/m³
Mineral Spirits	8052-41-3	PEL	400 ppm 2900 mg/m³
Monoethanolamine	141-43-5	PEL	500 ppm 6 mg/m³
Propane	74-98-6	PEL	3 ppm 1800 mg/m³ 1000 ppm
US. ACGIH Threshold Limit	Values		
Components	CAS Number	Туре	Value
Anhydrous Ammonia	7664-41-7	STEL	35 ppm
		TWA	25 ppm
Isobutane	75-28-5	STEL	1000 ppm
Isopropyl Alcohol	67-63-0	STEL	400 ppm
		TWA	200 ppm
Methylene Chloride	75-09-2	TWA	50 ppm
Mineral Spirits	8052-41-3	TWA	100 ppm
Monoethanolamine	141-43-5	STEL TWA	6 ppm 3 ppm

N/D — NOT DETERMINED

N/E --- NONE ESTABLISHED

N/R — NOT REGULATED

8. EXPOSURE CONTROLS / PERSONAL PROTECTION CONTINUED

Components	CAS Number	Туре	Value
Anyhdrous Ammonia	7664-41-7	STEL	27 mg/m ³
			35ppm
		TWA	18 mg/m ³
			25 ppm
Isobutane	75-28-5	TWA	1900 mg/m³
			800 ppm
Isopropyl Alcohol	67-63-0	STEL	1225 mg/m ³
			500 ppm
		TWA	980 mg/m ³
			400 ppm
Mineral Spirits	8052-41-3	Ceiling	1800 mg/m³
·		TWA	350 mg/m ³
Monoethanolamine	141-43-5	STEL	15 mg/m³
			6 ppm
		TWA	8 mg/m ³
			3 ppm
Propane	74-98-6	TWA	1800 mg/m³
·			1000 ppm
Biological Limit Values ACGIH Biological Exposure Indices			

Components	CAS Number	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol	67-63-0	40 mg/l	Acetone	Urine	*
Methylene Chloride	75-09-2	0.3 mg/l	Dichloromethane	Urine	*

* - For sampling details, please see the source document.

Appropriate Engineering controls: Good general ventilation (typically 10 air changed per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Hand protection: Wear appropriate chemical resistant gloves.

Skin protection

Other: Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection: If permissible levels are exceeded use NIOSH mechanical filter/organic vapor cartridge or an air-supplied respirator.

Thermal hazards: Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state:	Gas.
Form:	Aerosol. Compressed gas.
Color:	Not available.
Odor:	Not available.
Odor threshold:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.
Initial boiling point and boiling point range:	-43.78°F (-42.1°C) estimated
Flash point:	-99.4°F (-73.0°C) PROPELLANT estimated
Evaporation rate:	Not available.
Flammability (solid, gas):	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	10.8% estimated
Flammability limit - upper (%)	18.2% estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure:	2686.37 psig @ 70°F estimated
Vapor density:	Not available.
Relative density:	Not available.
Solubility(ies)	
Solubility (water):	Not available.
Partition coefficient (n-octanol/water):	Not available.
Auto-ignition temperature:	1004.51°F (540.28°C) estimated
Decomposition temperature:	Not available.
Viscosity:	Not available.
Other information:	
Specific gravity	0.216 estimated

10. STABILITY AND REACTIVITY

Reactivity:	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerization does not occur.
Conditions to avoid:	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials:	Strong oxidizing agents. Nitrates. Isocyanates. Fluorine. Chlorine.
Hazardous decomposition products:	No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure		
Ingestion:	Expected to be a low ingestion hazard.	
Inhalation:	May cause damage to organs through prolonged or repeated exposure by inhalation. Prolonged inhalation	
	may be harmful.	
Skin contact:	Causes skin irritation. Prolonged or repeated exposure may cause liver and kidney damage. These effects	
	have not been observed in humans.	
Eye contact:	Causes serious eye irritation.	

Symptoms related to the physical, chemical and toxicological characteristics: Dizziness. Nausea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological	enects	
Acute toxicity		
Components	Species	Test Results
Anhydrous Ammonia (CAS 766	64-41-7)	
Acute		
Inhalation		
LC50	Mouse	4230 ppm, If <1L: Consumer commodity hours
	Rat	7939 mg/m³
		4000 ppm, If <1L: Consumer commodity hours
Oral		
LD50	Rat	350 mg/kg
Isobutane (CAS 75-28-5)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 minutes
		52%, 120 minutes
	Rat	1355 mg/l
Isopropyl Alcohol (CAS 67-63-	0)	
Acute		
Dermal		
LD50	Rabbit	16.4 ml/kg, 24 hours
Inhalation		
LC50	Rat	> 10000 ppm, 6 hours
Oral		
LD50	Rat	5.84 g/kg
Methylene Chloride (CAS 75-0	9-2)	
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, Days
Inhalation		
LC50	Mouse	49 mg/l, 7 Hours

Information on toxicological effects

11. TOXICOLOGICAL INFORMATION CONTINUED

Monoethanolamine (CAS 141-43-5)

Acute		
Dermal		
LD50	Rabbit	2504 mg/kg, 24 Hours
		2.46 - 2.83 ml/kg, 24 Hours
Inhalation		
LC50	Rat	> 1.3 mg/l, 6 Hours
Oral		
LD50	Rat	1089 mg/kg
		1.07 ml/kg
Propane		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52%, 120 Minutes
	Rat	1355 mg/l
		658 mg/l, 4 Hours

*Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation:	Causes skin irritation.
Serious eye damage/eye irritation:	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization:	Not available.
Skin sensitization:	This product is not expected to cause skin sensitization.
Germ cell mutagenicity:	May cause genetic defects.
Carcinogenicity:	May cause cancer.
IARC Monographs. Overall Evaluation of Carcinogenici	ity
Methylene Chloride (CAS 75-09-2)	2B Possibly carcinogenic to humans.
OSHA Specifically Regulated Substances (29 CFR 1910).1001-1050)
Methylene Chloride (CAS 75-09-2)	Cancer
US. National Toxicology Program (NTP) Report on Carc	inogens
Methylene Chloride (CAS 75-09-2)	Reasonably anticipated to be a human carcinogen.
Reproductive toxicity:	This product is not expected to cuase reproductive or developmental effects.
Specific target organ toxicity - single exposure:	Not classified.
Specific target ogan toxicity - repeated exposure:	Repiratory system. Skin. Kidneys. Central nervous system. Eyes. Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard:	Not likely, due to the form of the product.
Chronic effects:	Prolonged inhalation may be harmful. May be harmful if absorbed through skin. Prolonged exposure may cause chronic effects. Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans. Cause damage to organs through prolonged or repeated exposure.
N/A — NOT APPLICABLE N/D — NOT DETERMINED	N/E — NONE ESTABLISHED N/R — NOT REGULATED N/L — NOT LISTED

12. ECOLOGICAL INFORMATION

Ecotoxicity: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Anhydrous Am	monia (CAS 7664-41-7)	Species	Test Results
Aquatic			
Fish	LC50	Chinook salmon	0.43 - 0.47 mg/l, 96 hours
		(Onchorhynchus tshawytscha)	
Isopropyl Alcoh	nol (CAS 67-63-0)		
Aquatic			
Algae	IC50	Algae	1000.0001 mg/L, 72 hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	>1400 mg/l, 96 hours
Methylene Chlo	oride (CAS 75-09-2)		
Aquatic			
Algae	IC50	Algae	500.0001 mg/L, 72 hours
Crustacea	EC50	Daphnia	1689.5 mg/L, 48 hours
		Water flea (Daphnia magna)	1250 mg/l, 48 hours
Fish	LC50	Fathead minnow	140.8 - 277.8 mg/l, 96 hours
		(Pimephales promelas)	
Monoethanolar	mine (CAS 141-43-5)		
Aquatic			
Algae	IC50	Algae	15 mg/L, 72 hours
Crustacea	EC50	Daphnia	65 mg/L, 48 hours
Fish	LC50	Fish	96 hours
		Rainbow trout, donaldson trout	114 - 196 mg/l, 96 hours
		(Oncorhynchus mykiss)	

*Estimates for product may be based on additional component data not shown.

Persistence and degradability: No data is available on the degradability of this product.

Bio-accumulative potential: No data available.

Partition coefficient n-octanol/wa	ter (log Kow)
------------------------------------	---------------

Isobutane	2.76
Isopropyl Alcohol	0.05
Methylene Chloride	1.25
Mineral Spirits	3.16 - 7.15
Monoethanolamine	-1.31
Propane	2.36

Mobility in soil: No data available.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. DISPOSAL CONSIDERATIONS

Disposal instructions: Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations: Dispose in accordance with all applicable regulations.

Hazardous waste code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Methylene Chloride (CAS 75-09-2)

Waste from residues/unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: disposal instructions).

U080

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN Number	
on number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before
	handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

i,			• /	•
I	F	٩	r	•

UN number	UN1950
UN proper shipping name	Aerosols, flammable,
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards:	No.
ERG Code:	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before
	handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging exceptions	LTD QTY

Page 10 of 13

14. TRANSPORT INFORMATION CONTINUED

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant:	No.
EmS:	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before
	handling.
Packaging exceptions	LTD QTY
Transport in bulk according to Annex II of	Not applicable.
MARPOL 73/78 and the IBC Code	





IATA; IMDG



15. REGULATORY INFORMATION

US federal regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4):			
Anhydrous Ammonia (CAS 7664-41-7)	Listed.		
Methylene Chloride (CAS 75-09-2)	Listed.		
SARA 304 Emergency release notification			
Anhydrous Ammonia (CAS 7664-41-7)	100 LBS		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)			
Methylene Chloride (CAS 75-09-2)	Cancer		
	Heart		
	Central nervous system		
	Liver		
	Skin irritation		
	Eye irritation		

15. REGULATORY INFORMATION CONTINUED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories			Immediate Hazard - Yes		
			Delayed Hazard - Yes		
			Fire Hazard - Yes		
			Pressure Hazard - Yes		
			Reactivity Hazard - No		
SARA 302 Extremely	hazardous subst	ance			
Chemical name	CAS number	Reportable quantity	Threshold planning	Threshold	Threshold
			quantity	planning quantity,	planning quantity,
				lower value	upper value
Anhydrous Ammonia	7664-41-7	100	500 lbs		
	75-56-9	100	10000 lbs		

SARA 311/312 Hazardous chemical: No.

SARA 313 (TRI reporting)		
Chemical name	CAS number	% by weight
Methylene Chloride	75-09-2	60 - 80
Anhydrous Ammonia	7664-41-7	0.1 - 1
Propylene Oxide	75-56-9	0.01 - 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methylene Chloride (CAS 75-09-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Anhydrous Ammonia (CAS 7664-41-7)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Anhydrous Ammonia (CAS 7664-41-7)

Isobutane (CAS 75-28-5)

Isopropyl Alcohol (CAS 67-63-0)

Methylene Chloride (CAS 75-09-2)

Mineral Spirits (CAS 8052-41-3)

Monoethanolamine (CAS 141-43-5)

Propane (CAS 74-98-6)

US New Jersey Worker and Community Right-to-Know Act

Anhydrous Ammonia (CAS 7664-41-7)

Isobutane (CAS 75-28-5)

Isopropyl Alcohol (CAS 67-63-0) Methylene Chloride (CAS 75-09-2) Mineral Spirits (CAS 8052-41-3)

Monoethanolamine (CAS 141-43-5)

Propane (CAS 74-98-6)

15. REGULATORY INFORMATION CONTINUED

US Pennsylvania Worker and Community Right-to-Know Law Anhydrous Ammonia (CAS 7664-41-7) Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Methylene Chloride (CAS 75-09-2) Mineral Spirits (CAS 8052-41-3) Monoethanolamine (CAS 141-43-5) Propane (CAS 74-98-6) **US Rhode Island RTK** Anhydrous Ammonia (CAS 7664-41-7) Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Methylene Chloride (CAS 75-09-2) Propane (CAS 74-98-6) **US.** California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance		
Diethanolamine (CAS 111-42-2)	Listed: June 22, 2012	
Methylene Chloride (CAS 75-09-2)	Listed: April 1, 1988	
Propylene Oxide (CAS 75-56-9)	Listed: October 1, 1988	

International Inventories

Country(s) or region	Inventory Name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in Chine(IECS)	No
Europe	European Inventory of Existing Commerical Chemical	No
	Substances (EINECS)	
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicated that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicated that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. OTHER INFORMATION

Disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text..

Revision Information: Product and Company Identification: Alternate Trade Names

Page 13 of 13