# RED BION

# SAFFTY DATA SHFFT

# CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

# FOR CHEMICAL EMERGENCY

Call ChemTrec day/night: 1-800-424-9300

# 1. IDENTIFICATION

PRODUCT NAME: 268 Hi-Strength Red Threadlocker

**DATE PREPARED:** June 15, 2015

PART NUMBER: 74563

MANUFACTURER: CHROMATE INDUSTRIAL CORPORATION 5250-A Naiman Parkway, Solon, OH 44139 • www.chromate.com

PRODUCT TYPE: Threadlocker

EMERGENCY TELEPHONE NUMBER OF THE COMPANY: (888) 567-2206

**RESTRICTIONS OF USE:** None identified.

PRODUCT INFORMATION TELEPHONE NUMBER: (888) 567-2206

**REGULATORY INFORMATION TELEPHONE NUMBER:** (888) 567-2206

TRANSPORTATION EMERGENCY TELEPHONE NUMBER: (800) 424-9300

NATIONAL POISON CENTER: (800) 222-1222

# 2. HAZARDS IDENTIFICATION

Emergency overview: WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

Hazard class: Hazard Category:

Skin irritationCategory 2Eye irritationCategory 2ASkin sensitizationCategory 1

Pictograms:



#### Precautionary statements:

Prevention: Avoid breathing dust or fumes. Wash thoroughly after handling. Contaminated work clothing should not be

allowed out of the workplace. Wear eye and face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation or rash occurs: Get

medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Not prescribed.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS number	Percentage*
Polyglycol dimethacrylate	Proprietary	30 - 60
Dimethacrylate ester	Proprietary	10 - 30
Methacrylate monomer	Proprietary	10 - 30
Rheological additive	Unknown	10 - 30
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Cumene hydroperoxide	80-15-9	1 - 5
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1
Cumene	98-82-8	0.1 - 1

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### **4 FIRST-AID MEASURES**

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical

attention.

Skin contact: Immediately flush skin with plent of water (using soap, if available). Remove contaminated clothing and

footwear. Wash clothing before reuse. Get medical attention.

Eye contact: Rinse immediately with plenty of water, also under eyelids, for at least 15 minutes. Get medical attention.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an

unconscious person. Get medical attention.

**Symptoms:** See section 11.

# 5. FIRE-FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperatures resulting in explosions

or rupture of storage containers.

Hazardous combustion products: Oxides of nitrogen. Oxides of carbon. Irritating organic vapors.

#### **6. ACCIDENTAL RELEASE MEASURES**

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

# 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe

vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

Storage: For safe storage, store at or below 38°C (100.4°F). Keep in a cool, well ventilated area away from heat,

sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Chromate Customer Service at (888) 567-2206.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Dimethacrylate ester	None	None	None	None
Methacrylate monomer	None	None	None	None
Rheological additive	10 mg/m³ TWA Total dust. 3 mg/m³ TWA Respirable fraction.	15 mg/m³ TWA Total dust. 5 mg/m³ TWA Respirable fraction.	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m³ TWA Inhalable dust. 3 mg/m³ TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m³ TWA	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m³) TWA (SKIN)	None
1-Acetyl-2-Phenylhydrazine	None	None	None	None
Cumene	50 ppm TWA	50 ppm (245 mg/m³) PEL (SKIN)	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves. Nitrile gloves.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid.
Color: Red.

Odor: Characteristic.
Odor threshold: Not available.
pH: Not applicable.

**Vapor pressure:** <5.0000000 mm hg (80°F (26.7°C))

**Boiling point/range:** >300°F (>148.9°C) None

Melting point/range: Not available.

Specific gravity: 1.1

Vapor density:Not available.Flash point:Product is a solid.Flammability/explosive limits - lower:Not available.Flammability/explosive limits - upper:Not available.Auto-ignition temperature:Not available.Evaporation rate:Not available.Solubility in water:Slight.

Partition coefficient (n-octanol/water): Not available.

VOC content: 0.88%; 9.70 g/l

Viscosity: Not available.

Decomposition temperature: Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition products: Oxides of nitrogen. Oxides of carbon. Irritating organic vapours

.

**Incompatible materials:** Strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

#### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

# Potential Health Effects/Symptoms

**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Polyglycol dimethacrylate	None	Allergen, Irritant
Dimethacrylate ester	None	Irritant, Allergen
Methacrylate monomer	None	No records
Rheological additive	None	No data
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
Cumene hydroperoxide	None	Allergen, Central Nervous system,
		Corrosive, Irritant, Mutagen
1-Acetyl-2-phenylhydrazine	None	Allergen, Blood, Kidney, Mutagen, Some
		evidence of carinogenicity
Cumene	Oral LD50 (RAT) = 2.91 g/kg	Central nervous system, Irritant, Lung
	Oral LD50 (RAT) = 1,400 mg/kg	
	Inhelation I CEO (DAT 4 h) 9000 nnm	

	,	,	0 0
Inhala	ation LC50	(RAT, 4 h)	= 8000 ppm

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Dimethacrylate ester	No	No	No
Methacrylate monomer	No	No	No
Rheological additive	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Cumene hydroperoxide	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No
Cumene	No	Group 2B	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated. Hazard class or division: None. Identification number: None. Packing group: None.

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated. Hazard class or division: None. Identification number: None. Packing group: None.

#### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated. Hazard class or division: None. Identification number: None. Packing group: None.

# 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis.

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Delayed Health, Immediate Health.

**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40 CFR 372). Cumene hydroperoxide (CAS# 80-15-9).

CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

#### **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

**Disclaimer:** The data contained herein are furnished for information only and are believed to be reliable. However, Chromate Industrial Corp. and its affiliates do not assume responsibility for any results obtained by persons over whose methods Chromate Industrial Corp. has no control. It is the user's responsibility for any results obtained by persons over whose methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of Chromate's products. In light of the foregoing, Chroamte Industrial Corp. specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Chromate's products. Chromate Industrial Corp. further disclaims any liability for consequential or incidental damages of any kind, including lost profits.